



TP-Link TL-SG108 network switch

Unmanaged L2 Gigabit Ethernet (10/100/1000) Black



Modelis: TL-SG108

Gamintojas: TP-LINK

EAN: 1210002616898

Prekės kodas: 604003

30.00€

Certification: CE, FCC ,RoHS | Operating relative humidity (H-H): 10 - 90% | Cable types supported: Cat5 | Cable types supported: Cat5e | Forwarding rate: 11.9 Mpps | Manual: Yes | Access Control List (ACL) IPv6 entries: 11 | User guide: Yes | Switch layer: L2 | Switching capacity: 16 Gbit/s | Jumbo frames support: Yes | Jumbo frames: 16000 | 10G support: No | Cable types supported: Cat4 | MAC address auto-aging supported: Yes | Store-and-forward: Yes | Cables included: AC | Power consumption (max): 3.3 W | Wall mountable: Yes | Multicast support: Yes | Switch type: Unmanaged | Full duplex: Yes | IGMP snooping: Yes | Height: 25 mm | Rack mounting: No | Flow control support: Yes | Cable types supported: Cat3 | Harmonized System (HS) code: 85176990 | Quality of Service (QoS) support: Yes | Depth: 101 mm | Power supply included: Yes | Width: 158 mm | Auto MDI/MDI-X:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Yes | Packet buffer memory: 1.5 MB | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | MAC address table: 4096 entries | GARP VLAN Registration Protocol (GVRP): Yes | Copper ethernet cabling technology: 10BASE-T | Auto-negotiation: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 90% | AC input frequency: 50 Hz | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3x | AC input voltage: 220 V | Operating temperature (T-T): 0 - 40 °C | LED indicators: Yes | Storage temperature (T-T): -40 - 70 °C | Input current: 0.6 A | Power over Ethernet (PoE): No | Quick start guide: Yes | Package type: Box | Networking standards: IEEE 802.3u | Product colour: Black