

TP-Link TL-WN781ND tinklo plokštė Vidinis WLAN 150 Mbit/ai

Gamintojas: **TP-LINK** · Modelis: **TL-WN781ND** · EAN: **1210002617697** · Prekės kodas: **604005**



13,90 €

Kaina su PVM

Be PVM: **11,49 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Bevielis
- ✓ PCI Express WLAN
- ✓ 150 Mbit/ai
- ✓ „Wi-Fi“ Viena juosta (2,4 GHz)
- ✓ Vidinis Lustų rinkinys: Atheros



Aprašymas

WHAT THIS PRODUCT DOES

TP-LINK TL-WN781N is designed to provide a complete end-to-end wireless performance from the server or server backbone to the switch infrastructure and down through to the desktop with the PCI Express connector. TL-WN781N Wireless Lite N PCI Express(x1) Adapter provides a wider compatibility, fitting with any standard PCI Express slot, x1, x2, x8, or x16. Compared with standard PCI network cards, it offers increased bandwidth, reliability and more functionality, allowing you to enjoy a fast and advanced connection, such as downloading, making internet call and video streaming.

Wireless N ---- Speed & Range

Complying with the IEEE 802.11n standard, TL-WN781N can easily establish a wireless network and get up to 9X the speed and 4X the range of conventional 11g products. Compared with legacy 54M products, TL-WN781N delivers performance enhancements, allowing you to have a more joyful surfing experience, including sharing files, watching streaming media.

WPA / WPA2 Encryptions ---- Advanced Security

As for the security of WI-FI connection, WEP encryption has been no longer the strongest and safest guards for outside intrusions. TL-WN781N provides WPA/WPA2 encryptions that are created by the WI-FI Alliance industry group, preventing the wireless network from outside threats.

Quick Setup Security

Compatible with WI-FI Protected Setup™ (WPS), TL-WN781N features Quick Security Setup (QSS) function, which is ideal for creating a WPA encrypted connection to prevent outside intrusion, and meanwhile maximize the management resources. Not only is this faster than normal security setups but more convenient in that you don't need to remember a password!

Detachable Antenna

TL-WN781N offers external antenna that can be rotated and adjusted in different directions to fit various operation environments, and can bring better performance than the internal antenna. For even more demanding applications, the antenna can be replaced with diverse antennas to show even greater flexibility and wider wireless coverage.

Features

- Adopts Align™ technology, with transmit speed up to 150Mbps;
- Provides PCI Express connector having a wider compatibility with any standard PCI Express slot;
- Supports QSS function, complying with WPS for worry free wireless security;
- Supports 64/128/152-bit WEP, WPA /WPA2/WPA-PSK/WPA2-PSK(TKIP/AES), supports IEEE 802.1X;
- Supports roaming technology, guaranteeing uninterrupted wireless connection;
- Supports Ad-Hoc/Infrastructure modes;
- Seamlessly compatible with 802.11n/b/g devices;
- Supports Windows 2000, Windows XP 32/64bit, Vista 32/64bit.

Techninė specifikacija

Ryšys	
Ryšio technologija	Bevielis
Priimančioji sąsaja	PCI Express
Sąsaja	WLAN
Tinklas	
Didžiausias duomenų perdavimo greitis	150 Mbit/ai
Tinklo standartai	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
„Wi-Fi“	Taip
„Wi-Fi“ dažnių juosta	Viena juosta (2,4 GHz)
Dažnių diapazonas	2,4 - 2,4835 GHz
Wi-Fi standartai	802.11b, 802.11g
WLAN duomenų perdavimo grečio palaikymas	11,54,150 Mbit/ai

Moduliacija	16-QAM, 64-QAM, CCK, DBPSK, DQPSK, OFDM
Apsaugos algoritmų palaikymas	128-bit WEP, 64-bit WEP, WPA-PSK, WPA2-PSK
Konstrukcija	
Vidinis	Taip
Produkto spalva	Žalia
Antena	Taip
Antenos konstrukcija	Išorinis
Antenos krypties tipas	Nekryptinis
Antenos stiprinimo lygis (max)	2 dBi
Lustų rinkinys	Atheros
Valdymo režimai	Infrastruktūros režimas
Sistemos reikalavimai	
Palaikomos „Windows“ operacinės sistemos	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Palaikoma operacinė sistema „Linux“	Taip
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	10 - 90%
Sandėliavimo santykinis drėgmės diapazonas	5 - 90%
Svoris ir matmenys	
Plotis	120,8 mm
Ilgis	78,5 mm
Aukštis	21,5 mm
Pakuotės duomenys	
Pakuotės plotis	200 mm

Pakuotės gylis	150 mm
Pakuotės aukštis	39 mm
Paketo svoris	150 g
Pakuotės turinys	
Šaltinis CD	Taip
Greito diegimo vadovas	Taip
Techninė informacija	
Atitikties sertifikatai	RoHS, Federalinė ryšių komisija (FCC), CE
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85176990
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	15,00cm × 4,00cm × 20,00cm
Svoris	0,17kg

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt