



Power Supply XILENCE 650 Watts Efficiency 80 PLUS GOLD PFC Active XN320

Modelis: XN320

Gamintojas: XILENCE

EAN: 4044953503306

Prekės kodas: 604028

83.99€

The Gaming GOLD Series is a PC power supply series with a fixed cable harness, as well as a 750W ARGB variant. The noble design with its black powder coating, the 120mm silent, black or transparent fan and the fan grille emphasizes the valuable character of this series.

The maximum voltage stability and the six integrated safety circuits ensure safe operation even in heated workflows or gaming sessions. The power supplies are suitable for the highest demands in gaming, multi-media application and streaming areas and have low power consumption during these intensive phases. The power supplies achieve the 80+ GOLD requirements.

- Whisper-quiet cooling: Large 120mm fan*
- Excellent airflow design for improved heat dissipation

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- With the following safety equipment:
- OVP (overvoltage protection)
- UVP (Undervoltage Protection)
- SCP (short circuit protection)
- OLP (overload protection)
- OTP (over temperature protection)
- OCP (overcurrent protection)
- Low standby power consumption
- High energy

Summary: Xilence Gaming Gold Series XP650R12. Total power: 650 W, AC input voltage: 200 - 240 V, Peak power: 650 W. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 55 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: RoHS, WEEE | Vendor Homepage: <https://www.xilence.net/en/power-supplies/221> | AC input frequency: 50 - 60 | AC input voltage: 200 - 240 | Combined power (+12V): 650 | Combined power (+3.3V): 100 | Combined power (+5V): 100 | Input current: 6.3 | Max output current (+12V1): 54.1 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Maximum input current (@220V): 6.3 | Peak power: 650 | Power Factor Correction (PFC) type: Active | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under power | Total power: 650 | Cabling type: Non-Modular | CPU power connector (4+4 pin): Yes | Motherboard power cable length: 550 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 6 | PCI Express power connectors (6+2 pin): 3 | 80 PLUS certification: 80 PLUS Gold | ATX version: 2.52 | Bearing technology: Hypro Bearing | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | On/off switch: Yes | Product colour: Black | Compliance certificates: RoHS/WEEE | Depth: 270 | Height: 95 | Weight: 2300 | Width: 195 | Sustainability certificates: ErP | Sustainability compliance: Yes | Product Net Weight: 2 | Shipping Box Height: 20.5 | Unit Calculated Volume: 0.005432 | Unit Calculated Weight: 2.17 | Units per Shipping Box: 1 | Model name: XN320 | XP650R12