



Power Supply XILENCE 450 Watts Efficiency 80 PLUS BRONZE PFC Active XN213

Modelis: XN213

Gamintojas: XILENCE

EAN: 4044953501661

Prekės kodas: 604029

47.99€

The new successful Gaming series combines high performance with a low noise level and high efficiency. The new DC/DC technology guarantees for increased efficiency and a maximum tension stability even during excessive gaming. Thanks to this high efficiency and the associated 80+ BRONZE certification high electricity costs are now a thing of the past. Six integrated safety circuits provide for an all-time safe operation and the sleeved main cable harness ensures order in the PC case.

- Extremely silent cooling: large 120mm fan
- semi-modular cable management
- Excellent air flow design for a better heat dissipation

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Low stand-by consumption
- High energy efficiency: 80+ BRONZE certified (complies with ErP2014 norm)
- Active-PFC

Summary: Xilence Performance A+ XN213. Total power: 450 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 50 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: RoHS, WEEE | Vendor Homepage: <https://www.xilence.net/en/power-supplies/120> | AC input frequency: 50 | AC input voltage: 200 - 240 | Combined power (+12V): 396 | Combined power (+3.3V): 100 | Input current: 10 | Max output current (+12V): 33 | Max output current (+3.3V): 20 | Max output current (+5V): 14 | Max output current (+5Vsb): 2 | Max output current (-12V): 0.5 | Power Factor Correction (PFC) type: Active | Power protection features: Over power/Over voltage/Short circuit/Under voltage | Total power: 450 | ATX power connector (20+4 pin): Yes | Cabling type: Non-Modular | CPU power connector (4+4 pin): Yes | Floppy disk drive connector: Yes | Floppy drive power connector: 1 | Motherboard power cable length: 500 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 5 | PCI Express connector: Yes | PCI Express power connectors (6+2 pin): 1 | Peripheral (Molex) power connectors (4-pin): 3 | 80 PLUS certification: 80 PLUS Bronze | ATX version: 2.4 | Bearing technology: FDB | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Fan location: Top | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Compliance certificates: RoHS/WEEE | Package type: Box | Sustainability certificates: ErP | Product Net Weight: 1.5 | Shipping Box Height: 23 | Unit Calculated Volume: 0.006132 | Unit Calculated Weight: 1.92 | Units per Pallet: 0 | Units per Shipping Box: 8 | Model name: XN213 | XP450R10