

iiyama T1532MSC-B5X computer monitor 38.1 cm (15") 1024 x 768 pixels XGA LED Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **T1532MSC-B5X** · EAN: **4948570115983** · Prekės kodas: **606402**



258,90 €

Kaina su PVM

Be PVM: **213,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 38.1 cm (15") Black
- ✓ Built-in speaker(s)
- ✓ HDMI DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Response time: 8 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 1024 x 768 pixels XGA Panel type: TN
- ✓ Energy efficiency class (SDR): E ErP CB, CE, EAC, REACH, RoHS, VCCI, WEEE



Aprašymas

The ProLite T1532MSC-B5X 15" multi-touch screen is based on projected capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the touchscreen with an adjustable stand offering full 90 degree positioning angles. Menu buttons are located on the side of the screen which can be locked to prevent tampering and includes a handy function to deactivate the touchscreen for cleaning. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours.

Techninė specifikacija

Specifications	
Sandėlio grupė	Monitore [+1510][-138]
Display	
Display diagonal	38.1 cm (15")
Display resolution	1024 x 768 pixels
Native aspect ratio	4:3
Display technology	LED
Touchscreen	Yes
HD type	XGA
Panel type	TN
Response time	8 ms
Screen shape	Flat
Contrast ratio (typical)	700:1
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	370 cd/m²
Display brightness	330 cd/m²
Response time measurement type	GTG (Gray to Gray)
Aspect ratio	4:3
Viewing angle, horizontal	170°
Viewing angle, vertical	160°
Pixel pitch	0.297 x 0.297 mm
Horizontal scan range	31 - 60 kHz
Vertical scan range	56 - 75 Hz
Viewable size, horizontal	30.4 cm
Viewable size, vertical	22.8 cm
Display diagonal (metric)	38 cm
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Windows operating systems supported	Yes

Linux operating systems supported	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Built-in microphone	No
Design	
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
HDMI	Yes
USB Touch port	Yes
USB Touch ports quantity	1
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
HDCP	Yes
Network	
Ethernet LAN	No
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	7
Plug and Play	Yes
LED indicators	Yes

Power

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	10.2 kWh
Power consumption (typical)	16 W
Power consumption (standby)	2 W
Power consumption (off)	1 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Weight & dimensions

Width (with stand)	351 mm
Depth (with stand)	202 mm
Height (with stand)	306.5 mm
Weight (with stand)	4.5 kg

Packaging data

USB cable length	1.8 m
------------------	-------

Packaging content

Cables included	AC, USB, HDMI, DisplayPort, Audio
Quick start guide	Yes
Audio cable length	1.8 m
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m

Sustainability

Sustainability certificates	ErP
-----------------------------	-----

Other features

International Protection (IP) code	IP54
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Brightness	330 cd/m²
Packaging content	Touch Panel Driver Disk (CD-ROM)
Active display area (W x H)	304.1 x 228.1 mm

Weight	4.5 kg
Height	306.5 mm
Width	351 mm
Depth	202 mm
Compliance certificates	CB, CE, EAC, REACH, RoHS, VCCI, WEEE
Certification	CB, CE, TÜV, VCCI, EAC
User controls	contrast, brightness, auto adjust, H.position, V.position, H.size, fine, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute
Touch method	stylus, finger, glove (latex)
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Mute, Select, Power
Supplied AC adapter type	AC
Logistics data	
Harmonized System (HS) code	85285210