

iiyama ProLite TF1934MC-B2X computer monitor 48.3 cm (19") 1280 x 1024 pixels LED Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **TF1934MC-B2X** · EAN: **4948570113743** · Prekės kodas: **606406**



309,91 €

Kaina su PVM

Be PVM: **256,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48.3 cm (19") Black
- ✓ Screen shape: Flat
- ✓ Response time: 14 ms
- ✓ 1280 x 1024 pixels Panel type: IPS



Aprašymas

The ProLite TF1934MC-B2X 19" multi touch screen is based on projective capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The IPS matrix guarantees high performance with accurate and consistent colour reproduction, and wide viewing angles. The touch function remains unaffected even if the glass is scratched. The screen is IP65 rated which means it is dust and water resistant. For ease of installation in any environment the ProLite TF1934MC-B2X comes equipped with external mounting brackets making it an ideal solution for kiosk integrators and Instore Retail.

Techninė specifikacija

Specifications

Sandėlio grupė

Monitore [+1510][-138]

Display

Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LED
Touchscreen	Yes
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.78 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Display brightness	225 cd/m²
Aspect ratio	5:4
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.294 x 0.294 mm
Viewable size diagonal	48 cm
Digital horizontal frequency	31.4 - 80 kHz
Digital vertical frequency	56 - 75 Hz
Display diagonal (metric)	48 cm
Separate H/V sync	Yes

Performance

NVIDIA G-SYNC	No
AMD FreeSync	No
Windows operating systems supported	Yes
Number of simultaneous touchpoints (Windows 7)	10

Multimedia

Built-in camera	No
Megapixel (approx.)	1.3 MP
Built-in microphone	No

Design

Product colour	Black
----------------	-------

Ports & interfaces

Number of upstream ports	1
VGA (D-Sub) ports quantity	1
DVI port	Yes
DVI-D ports quantity	1
HDMI ports quantity	0
DisplayPorts quantity	0

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	8
Plug and Play	Yes

Power

Power consumption (typical)	20 W
Power consumption (standby)	2 W
Power supply type	AC/DC

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width (without stand)	416 mm
Depth (without stand)	46.5 mm
Height (without stand)	344.5 mm
Weight (without stand)	4.5 kg

Packaging content

Cables included	AC, DVI, USB, VGA
Quick start guide	Yes

Other features

International Protection (IP) code	IP65
Display viewable area (HxV)	376.5 x 301.1 mm
Power management	Yes
Certification	CE, CB, TÜV-Bauart, CU, cULus
Supplied AC adapter type	AC
Logistics data	
Harmonized System (HS) code	85285210