



# Cudy AP1300 Outdoor 1167 Mbit/s White Power over Ethernet (PoE)



Modelis: AP1300 Outdoor

Gamintojas: CUDY

EAN: 6971690792893

Prekės kodas: 606696

---

## 73.99€

---

Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux | Bundled software: Cudy Software | AC input voltage: 100 - 240 V | Ethernet LAN data rates: 100 | MIMO: Yes | Network address translation (NAT): Yes | Bluetooth: No | Maximum data transfer rate: 1167 Mbit/s | AC input frequency: 50/60 Hz | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | 2.4 GHz: Yes | Antenna type: External | Networking standards: IEEE 802.3at | Security algorithms: WPA2 | Operating modes: Wireless Access Point, Wireless Router, Wireless Extender, WISP | Ethernet LAN data rates: 1000 Mbit/s | Antenna connector type: RP-SMA | Processor frequency: 880 MHz | Quick start guide: Yes | WAN connection: Wi-Fi | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Weight: 865 g | Number of SSID supported: 8 | Web-based management: Yes | MAC address filtering: Yes | Wireless isolation: Yes | Networking standards: IEEE 802.11a | Ethernet LAN (RJ-45) ports: 1 | Security algorithms: WPA | Fit AP mode features: Mesh networking | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

IEEE 802.3af | DHCP client: Yes | Operating temperature (T-T): -20 - 60 °C | Networking standards: IEEE 802.11ac | Product colour: White | Package weight: 865 g | Wi-Fi Multimedia (WMM)/(WME): Yes | WAN connection: Ethernet (RJ-45) | Height: 240 mm | Reset button: Yes | 5 GHz: Yes | Output voltage: 24 - 57 V | Power over Ethernet (PoE) type supported: Active PoE | Power over Ethernet (PoE) type supported: Passive PoE | Products per shipping (inner) case: 20 pc(s) | Networking standards: IEEE 802.11b | Service Set Identifier (SSID) features: Multiple SSIDs | Package width: 324 mm | Virtual LAN features: Tagged VLAN | Number of users: 128 user(s) | Parental control: Yes | Depth: 53.7 mm | Placement: Pole, Wall | Syslog: Yes | Rate limiting: Yes | Wireless range: 170 m | IP address filtering: Yes | Cables included: UTP | Package depth: 107 mm | AC adapter included: No | PoE adapter included: Yes | Maximum data transfer rate (5 GHz): 867 Mbit/s | Antennas quantity: 2 | Manual languages: Multi | Antenna included: Yes | Channel bandwidth: 80 MHz | Power consumption (typical): 11 W | BeamForming: Yes | Built-in processor: Yes | International Protection (IP) code: IP65 | Band steering: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Warranty period: 1 year(s) | MIMO type: Multi User MIMO | Operating relative humidity (H-H): 10 - 90% | Antenna features: Detachable antenna | Width: 100 mm | Fast roaming: Yes | IGMP snooping: Yes | 6 GHz: No | Power over Ethernet (PoE): Yes | Chipset: MT7621DA+MT7613B+MT7603E | Internal memory: 128 MB | Maximum outdoor range: 170 m | WPS push button: Yes | Package height: 86 mm | Mounting kit: Yes | VLAN support: Yes | Dynamic DNS (DDNS): Yes | Port forwarding: Yes | Flash memory: 16 MB | Antenna width: 2.16 cm | Antenna depth: 1.55 cm | Antenna height: 19.8 cm | Warnings: Do not expose to prolonged moisture. | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Warnings: Avoid direct contact with water.