

Lindy 30403 power cable Black 5 m IEC C14 IEC C15

Gamintojas: **LINDY** · Modelis: **30403** · EAN: **4002888304030** · Prekės kodas: **606789**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Rated 10A / 250V AC with heat resistance up to 120°C
- ✓ Designed for equipment requiring hot conditioning or continuous high-temperature operation
- ✓ Complies with IEC 60320 and international safety standards
- ✓ Durable molded connectors and flexible PVC outer jacket

Aprašymas

The IEC C14 to IEC C15 Mains Extension Cable is a professional-grade power solution designed to extend the connection between equipment requiring secure, heat-resistant AC power. Featuring an IEC C14 plug (male) to IEC C15 connector (female) configuration, this cable is ideal for use in data centers, broadcast systems, and Pro AV environments where reliability and performance are critical.

The Lindy C14 to C15 Extension cable supports up to 10A at 250V AC and is specifically designed for high-temperature applications up to 120°C. The C15 connector includes a notch and higher heat tolerance compared to the standard C13, making it suitable for equipment that undergoes hot conditioning or operates continuously under elevated temperatures such as servers, UPS systems, and network switches.

The robust molded connectors and flexible, flame-retardant PVC jacket ensure durability and safe operation during extended use. Each cable is electrically tested and hot-condition rated, guaranteeing stable power transmission even in demanding environments where thermal management is essential.

Available in multiple lengths, the IEC C14 to C15 Mains Extension Cable supports efficient rack organization, optimized airflow, and dependable performance in mission-critical installations.

Techninė specifikacija

Specifications

Sandėlio grupė

PC Power Cables [+33][-74]

Features

Product colour	Black
Connector 1 gender	Male
Connector 2 gender	Female
Cable length	5 m
Connector 1	IEC C14
Connector 2	IEC C15
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Nickel
Jacket material	Polyvinyl chloride (PVC)
Conductor material	Copper
Cable type	H05VV-F 3G 1
Number of cable cores	3
Core size	1 mm ²

Power

Input voltage	250 V
Input current	10 A

Operational conditions

Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 70 °C

Certificates

Compliance certificates	CE, RoHS, REACH
-------------------------	-----------------

Weight & dimensions

Diameter	6.8 mm
----------	--------

Packaging data

Quantity per pack	1 pc(s)
Package type	Polybag

Technical details

Housing material	Polyvinyl chloride (PVC), Polybutylene terephthalate (PBT)
------------------	--

Matmenys ir svoris

Matmenys (l × p × A)	21,00cm × 18,00cm × 3,00cm
----------------------	----------------------------