

NEC MultiSync M321 Digital signage flat panel 81.3 cm (32") LCD 450 cd/m² Full HD Black

Gamintojas: **SHARP** · Modelis: **60005288** · EAN: **5028695123663** · Prekės kodas: **608072**



316,90 €

Kaina su PVM

Be PVM: **261,90 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Landscape and Portrait orientation allows for flexibility of installation dependent on your needs
- ✓ Bidirectional and Full External Control allows for easy integration into control systems via LAN or RS232C
- ✓ 450 cd/m2 brightness and HDR compatibility will capture the attention of audience in almost any situation
- ✓ Integrated Media Player allows for audio, video or image playback via USB
- ✓ Failover Capabilities with full Input Detect functionality allow peace of mind as the display will automatically switch to a secondary or tertiary source if the primary source fails
- ✓ Full 3 year commercial warranty to allow for peace of mind and protection of your investment
- ✓ NaViSet Administrator 2 Free software solution that greatly eases administration and management of larger display device installations



Aprašymas

Create pixel-perfect imagery with the high-end panel quality of the fully professional NEC M321 large format display. By focusing on customer needs while also offering professional reliability, the M series displays give customers a digital signage display lineup without all the costs. This M series display can support both landscape and portrait orientations while also containing a an anti-glare panel to allow for easy readability for true commercial applications. The new product contains a full metal mechanical chassis, allowing for a more robust design necessary for commercial applications while maintaining the attractive aesthetics that allow the focus of onlookers to be on what matters – the message. Simple and targeted

connectivity options allow customers to have the up-to-date options that they need while not having to overpay for excess and unused interfaces. The NEC M series boasts 450 cd/m² brightness which is ideal for a majority of digital signage applications in corporate, higher education, restaurant, retail and grocery store environments when the focus should be on the message, not the budget.

Techninė specifikacija

Specifications	
Sandėlio grupė	Large Format Displays [+248] [-36]
Display	
Display diagonal	81.3 cm (32")
Display technology	LCD
Display resolution	1920 x 1080 pixels
Display brightness	450 cd/m²
HD type	Full HD
Touchscreen	No
Panel type	IPS
LED backlight	Yes
Response time	8 ms
Contrast ratio (typical)	1100:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	16.78 million colours
Pixel pitch	0.364 x 0.364 mm
Active display area (W x H)	698.4 x 392.9 mm
Horizontal scan range	15 - 136 kHz
Vertical scan range	23 - 76 Hz
High Dynamic Range (HDR) supported	Yes
Haze rate	28%
Ports & interfaces	
HDMI ports quantity	2
DVI port	No
DisplayPorts quantity	1
USB port	Yes
VGA (D-Sub) input ports	1
Ethernet LAN (RJ-45) ports	1
Number of speaker outputs	1

RS-232C	Yes
Remote (IR) input	1
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	10 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Panel mounting interface	100 x 100,200 x 200 mm
Bezel width (bottom)	1.72 cm
Bezel width (side)	1.19 cm
Bezel width (top)	1.19 cm
Performance	
Purpose	Universal
Power	
Power consumption (typical)	40 W
Power consumption (standby)	0.5 W
AC input voltage	100 - 240 V
Computer system	
Computer system	No
Built-in processor	No
Weight & dimensions	
Weight	6.3 kg
Width (with stand)	726.6 mm
Depth (with stand)	267.7 mm
Height (with stand)	476.3 mm
Weight (with stand)	8.2 kg
Packaging data	
Package width	870 mm
Package depth	160 mm

Package height	527 mm
Package weight	9.8 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC, HDMI
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 80%
Logistics data	
Harmonized System (HS) code	85285210
Network	
Ethernet LAN	Yes
Matmenys ir svoris	
Svoris	8,90kg