

# Seagate IronWolf Pro ST4000NT001 internal hard drive 4 TB 7200 RPM 256 MB 3.5"

Gamintojas: **SEAGATE** · Modelis: **ST4000NT001** · EAN: **8719706432351** · Prekės kodas: **609434**



## 261,90 €

Kaina su PVM

Be PVM: **216,45 €**

[Sandėlyje](#)



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 4 TB 3.5" 7200 RPM
- ✓ NAS HDD
- ✓ Storage drive buffer size: 256 MB
- ✓ 6 Gbit/s
- ✓ Uncorrectable Bit Error Rate (UBER): < 1 per 10<sup>15</sup> bits read
- ✓ 650 g



## Aprašymas

IronWolf Pro drives are engineered to deliver 24x7 performance, reliability, and dependability in multi-bay, multi-user commercial and enterprise RAID storage solutions. Total peace of mind with five-year limited warranty, complimentary three-year Rescue Data Recovery Services, and IronWolf Health Management.

## Techninė specifikacija

### Specifications

Sandėlio grupė

HDDs [+39] [-59]

### Features

|                                     |                                    |
|-------------------------------------|------------------------------------|
| HDD capacity                        | 4 TB                               |
| HDD speed                           | 7200 RPM                           |
| HDD size                            | 3.5"                               |
| Type                                | HDD                                |
| Component for                       | NAS                                |
| Storage drive buffer size           | 256 MB                             |
| HDD interface transfer rate         | 6 Gbit/s                           |
| HDD sustained transfer rate         | 250 MiB/s                          |
| Uncorrectable Bit Error Rate (UBER) | < 1 per 10 <sup>15</sup> bits read |
| Rotational Vibration (RV) sensors   | Yes                                |
| Workload rate limit                 | 550 TB/year                        |
| Noise level (idle)                  | 28 dB                              |
| Mean time between failures (MTBF)   | 2000000 h                          |
| <b>Power</b>                        |                                    |
| Power consumption (typical)         | 8.7 W                              |
| Power consumption (standby)         | 1 W                                |
| Power consumption (off)             | 1 W                                |
| Power consumption (idle)            | 5.5 W                              |
| Operating voltage                   | 5 / 12 V                           |
| Start-up current                    | 2 A                                |
| <b>Operational conditions</b>       |                                    |
| Operating temperature (T-T)         | 0 - 65 °C                          |
| Storage temperature (T-T)           | -40 - 70 °C                        |
| Non-operating vibration             | 2.27 G                             |
| Operating shock                     | 70 G                               |
| Non-operating shock                 | 300 G                              |
| <b>Weight &amp; dimensions</b>      |                                    |
| Width                               | 101.8 mm                           |
| Height                              | 26.1 mm                            |
| Depth                               | 147 mm                             |
| Weight                              | 650 g                              |
| <b>Matmenys ir svoris</b>           |                                    |
| Matmenys (I × P × A)                | 15,00cm × 3,00cm × 10,00cm         |
| Svoris                              | 0,65kg                             |