

Optoma HZ41HDR Standard throw projector 4400 ANSI lumens DLP 1080p (1920x1080) 3D Black

Gamintojas: **OPTOMA** · Modelis: **E3P7PK1E122** · EAN: **5055387600607** · Prekės kodas: **616550**



892,90 €

Kaina su PVM

Be PVM: **737,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Supported graphics resolutions: 640 x 480 (VGA) | Vertical scan range: 24 - 120 Hz | Supported graphics resolutions: 1280 x 800 (WXGA) | HDMI ports quantity: 2 | Noise level: 31 dB | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1600 x 1200 (UXGA) | Supported graphics resolutions: 1024 x 768 (XGA) | Built-in display: No | 3D: Yes | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Full HD: Yes | Supported graphics resolutions: 1280 x 1024 (SXGA) | Package weight: 4.3 kg | Supported graphics resolutions: 1280 x 768 (WXGA) | Cables included: AC | Cable lock slot: Yes | Power consumption (max): 150 W | Power source: AC | Cable lock slot type: Kensington | Operating temperature (T-T): 0 - 40 °C | Weight: 2.9 kg | AC input voltage: 100 - 240 V | Operating altitude: 0 - 2500 m | Contrast ratio (dynamic): 2000000:1 | Horizontal scan range: 15 - 135 kHz | Product colour: Black | Native aspect ratio: 16:9 | USB 2.0 ports quantity: 1 | Operating relative humidity (H-H): 0 - 80% | Manual: Yes | AC input frequency: 50 - 60 Hz | Service life of light source: 30000 h | Number of colours: 1.073 billion colours | Projection distance: 1 - 10 m | Projector native resolution: 1080p (1920x1080) | Number of built-in speakers: 1 | HDMI connector type: Full-size | Projector brightness: 4400 ANSI lumens | Power consumption (economy mode): 110 W | Supported aspect ratios: 4:3 | Auto power off: Yes | High Dynamic Range (HDR) supported: Yes | Supported aspect ratios: 16:10 | Password protection: Yes | Keystone correction, horizontal: -30 - 30° | Supported aspect ratios: 16:9 | Keystone correction, vertical: -30 - 30° | Zoom type: Manual | Serial interface type: RS-232, RJ-45 | Export Control Classification Number (ECCN): EAR99 | Offset: 116% | USB 2.0 Type-A ports quantity: 2 | Video colour modes: Game | Light source type: Laser | Throw ratio: 1.48:1 ~ 1.62:1 | Zoom ratio: 1.1:1 | Projection technology: DLP | Screen size compatibility: 762 - 7620 mm (30 - 300") | Uniformity: 75% | Height: 114 mm | Width: 274 mm | HDMI version: 2.0 | Headphone outputs: 1 | DVI port: No | Card reader integrated: No | VGA (D-Sub) ports quantity: 1 | Analog signal format system: PAL D | Analog signal format system: SECAM B | Analog signal format system: PAL H | Analog signal format system: PAL N | Number of OSD languages: 25 | Market positioning: Presentation | On Screen Display (OSD): Yes | Harmonized System (HS) code: 8528.62 | Built-in speaker(s): Yes | Analog signal format system: SECAM K | Product type: Standard throw projector | Ethernet

LAN: No | Analog signal format system: NTSC M | Analog signal format system: PAL M | Focal length range: 21.86 - 24 mm | Remote control included: Yes | Analog signal format system: SECAM G | Depth: 216 mm | Analog signal format system: SECAM D | Analog signal format system: NTSC J | Power consumption (standby): 0.5 W | Batteries included: Yes | Supported video modes: 1080i | Analog signal format system: SECAM L | Supported video modes: 576p | Supported video modes: 576i | Supported video modes: 720p | Analog signal format system: PAL B | Analog signal format system: PAL G | Supported video modes: 480p | Supported video modes: 1080p | Contrast ratio (typical): 2500000:1 | RMS rated power: 15 W | Analog signal format system: PAL I | Analog signal format system: SECAM K1 | Supported video modes: 480i

Techninė specifikacija

Specifications	
Sandėlio grupė	Business projectors [+8][-10]
Matmenys ir svoris	
Matmenys (I × P × A)	40,00cm × 28,00cm × 16,00cm
Svoris	4,27kg