

TP-Link Omada AX3000 Indoor/Outdoor WiFi 6 Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP650 D120-Outdoor** · EAN: **8885020625066** · Prekės kodas: **617145**



210,90 €

Kaina su PVM

Be PVM: **174,30 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior WiFi 6 Speeds: 2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz
- ✓ Directional Ultra-Range Coverage: Equipped with built-in high-gain directional antennas to deliver precise and extended coverage
- ✓ Ideal for Warehouses and Outdoor Scenes: Features an IP68 waterproof enclosure with -30°C to +70°C operating range
- ✓ 802.11k/v/r Seamless Roaming: Ensures uninterrupted connectivity for AGVs and handheld scanners
- ✓ Flexible Deployment: Supports 802.3at PoE and Omada Mesh technology
- ✓ Centralized Cloud Management: Control everything from a single interface anywhere via the Omada app or Web UI



Aprašymas

Omada AX3000

Indoor/Outdoor WiFi 6 Access Point

Designed for Warehouses

The EAP650 D120-Outdoor features a durable, fully sealed IP68 weatherproof enclosure, making it dustproof and capable of withstanding submersion in water. It is ideal for warehouse environments.

Elevate WiFi Experience for Shelf Areas with Directional Antennas

Equipped with 4× built-in dual-band directional antennas with high gain to ensure the optimal WiFi experience ideal for precise and extended coverage.

Stay Smooth with Seamless Roaming

Ensure users enjoy uninterrupted steaming when moving around by switching clients automatically to the access points with the optimal signals.

Techninė specifikacija

Specifications	
Sandėlio grupė	Accesspoints [+288][-30]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	3000 Mbit/s
Maximum data transfer rate (2.4 GHz)	574 Mbit/s
Maximum data transfer rate (5 GHz)	2402 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Frequency band	2.4 - 5 GHz
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Cabling technology	10/100/1000Base-T(X)
Number of users	250 user(s)
Bluetooth	Yes
Automatic channel selection	Yes
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Virtual LAN features	SSID-based VLAN assignment
Band steering	Yes
Airtime Fairness (ATF)	Yes
Maximum indoor range	500 m
Security	
Security algorithms	SNMP, SNMPv2, SNMPv3
MAC address filtering	Yes
Remote Authentication Dial-In User Service (RADIUS)	Yes
Management features	
Web-based management	Yes

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
----------------------------	---

Power

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
AC input voltage	48 V

Design

Placement	Ceiling, Wall
Product colour	White

Antenna

Antenna type	Internal
Antenna direction type	Directional
Antennas quantity	4
Antenna gain level (max)	10 dBi

Weight & dimensions

Width	230 mm
Depth	207.5 mm
Height	58 mm

Packaging content

Quantity per pack	1 pc(s)
Mounting kit	Yes
Quick start guide	Yes

Other features

Horizontal beam width	120°
Vertical beam width	30°

Matmenys ir svoris

Matmenys (I × P × A)	36,00cm × 8,00cm × 26,00cm
----------------------	----------------------------