



Cudy AC1300 White Power over Ethernet (PoE)



Modelis: AP1300

Gamintojas: CUDY

EAN: 6971690792022

Prekės kodas: 619164

44.00€

Compatible operating systems: Windows, MAC OS, NetWare, UNIX, Linux | Bundled software: Cudy Software | DHCP client: Yes | Placement: Ceiling, Wall | Ethernet LAN (RJ-45) ports: 1 | Maximum data transfer rate: 1167 Mbit/s | Operating temperature (T-T): -10 - 65 °C | Ethernet LAN data rates: 100 | Mounting kit: Yes | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | Product colour: White | AC adapter included: Yes | Processor frequency: 880 MHz | Quick start guide: Yes | Power consumption (max): 11 W | Weight: 395.6 g | Security algorithms: WPA | 5 GHz: Yes | Networking standards: IEEE 802.11b | Package weight: 1.51 kg | WAN connection: Ethernet (RJ-45) | Networking standards: IEEE 802.3af | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | Bluetooth: No | 2.4 GHz: Yes | Reset button: Yes | Package width: 283 mm | Networking standards: IEEE 802.3at | Security algorithms: WPA2 | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3ab | Package depth: 238 mm | Web-based management: Yes | MAC address filtering: Yes | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.11g |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Networking standards: IEEE 802.11n | Antenna type: Internal | LED indicators: Yes | Operating relative humidity (H-H): 10 - 90% | AC input voltage: 100 - 240 V | Quantity per pack: 1 pc(s) | DC-in jack: Yes | MIMO type: Multi User MIMO | Flow control support: Yes | Internal memory: 128 MB | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Products per shipping (inner) case: 20 pc(s) | IP address filtering: Yes | Width: 232 mm | IGMP snooping: Yes | Height: 232 mm | Flash memory: 16 MB | Depth: 57.1 mm | Built-in processor: Yes | Antenna direction type: Omni-directional | VLAN support: Yes | Cabling technology: 10/100/1000Base-T(X) | Antennas quantity: 4 | Package height: 68 mm | Rate limiting: Yes | Full duplex: Yes | Internal: No | Output voltage: 12 V | Output current: 1 A | Maximum data transfer rate (5 GHz): 867 Mbit/s | Band steering: Yes | Fit AP mode features: Mesh networking | Parental control: Yes | Virtual LAN features: Tagged VLAN | Service Set Identifier (SSID) features: Multiple SSIDs | Manual languages: Multi | Compliance certificates: CE | 6 GHz: No | Warnings: Avoid direct contact with water. | Warnings: Do not expose to prolonged moisture. | Syslog: Yes | Warranty period: 1 year(s) | Sustainability compliance: Yes | Power over Ethernet (PoE) type supported: Passive PoE | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | PoE adapter included: No | DC voltage range: 24 - 57 V