



# Cudy AP3000\_P wireless access point 2976 Mbit/s White Power over Ethernet (PoE)



Modelis: AP3000\_P

Gamintojas: CUDY

EAN: 6971690793289

Prekės kodas: 619165

## 98.99€

Compatible operating systems: Microso Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux | Bundled software: Cudy Software | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Antenna type: Internal | Band steering: Yes | Height: 57.1 mm | Airtime Fairness (ATF): Yes | Cables included: UTP | Warnings: Do not expose to prolonged moisture. | Channel bandwidth: 160 MHz | 5 GHz: Yes | Maximum data transfer rate: 2976 Mbit/s | Quick start guide: Yes | Ethernet LAN data rates: 1000 Mbit/s | Networking standards: IEEE 802.11ax | Ethernet LAN data rates: 2500 Mbit/s | Networking standards: IEEE 802.11ac | WAN connection: Ethernet (RJ-45) | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.3at | Package weight: 1.01 kg | Rate limiting: Yes | Ethernet LAN data rates: 100 | Power over Ethernet (PoE) type supported: Active PoE | Warnings: Avoid direct contact with water. | MIMO: Yes | Weight: 489.6 g | Package height: 68 mm | Built-in processor: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Antennas quantity: 5 | Service Set Identifier (SSID) features: Multiple SSIDs | Mounting kit: Yes |  
Antenna direction type: Omni-directional | Processor frequency: 1300 MHz | Product colour: White |  
Operating relative humidity (H-H): 10 - 90% | Output voltage: 12 V | Operating temperature (T-T): 0 -  
40 °C | Ethernet LAN (RJ-45) ports: 1 | Maximum data transfer rate (2.4 GHz): 574 Mbit/s | Flash  
memory: 256 MB | Warnings: Electronic products should be recycled at specialist electronic waste  
collection facilities. | Placement: Ceiling, Wall | 2.4 GHz: Yes | Storage temperature (T-T): -40 - 70 °C |  
Quality of Service (QoS) support: Yes | Spread spectrum method: OFDMA | Power over Ethernet  
(PoE): Yes | Package width: 283 mm | AC adapter included: No | Wi-Fi Multimedia (WMM)/(WME): Yes  
| Package depth: 238 mm | Depth: 232 mm | Width: 232 mm | Fast roaming: Yes | Security  
algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | MIMO type: Multi User MIMO |  
Maximum data transfer rate (5 GHz): 2402 Mbit/s | PoE adapter included: Yes | Security algorithms:  
WPA | Security algorithms: WPA2 | 6 GHz: No | BeamForming: Yes