Cudy FS1010PG network switch Unmanaged Fast Ethernet (10/100) Power over Ethernet (PoE) Black

Gamintojas: **CUDY** · Modelis: **FS1010PG** · EAN: **6971690791254** · Prekės kodas: **619171**



39.91€

Kaina su PVM

Be PVM: **32.98€**

In Stock

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8× FE with 802.at/af Mode A PoE
- ✓ 2× Uplink GbE
- ✓ 120W Power Supply
- ✓ Extend On/Off, VLAN On/Off
- ✓ Watchdog On/Off
- ✓ PoE Max Status LED
- ✓ 200×118×44 mm (7.87×4.65×1.73'')



Aprašymas

Reliable PoE for 24/7 Consistent Operation

IEEE 802.3at/af. Up to 30W Per Port.
Each PoE port delivers up to 30W of power, making it suitable for access points, IP cameras, digital signage, and most other PoE devices.

PoE Auto Recovery

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Turn on the Watchdog function to monitor port activity. If a connected device freezes and stops transmitting data for 5 minutes, the Watchdog will automatically reboot the corresponding PoE port.

Simplify PoE Management

Extend PoE Reach. Enhance Client Security.

VLAN Isolates Downlink Ports for Improved Safety

Turn on the VLAN mode to prevent client-side hacking, preventing sensitive data from leaking. The downlink clients will only be able to communicate with the uplink devices.

Extend for 250 m Transmission

For long-distance networking, enable the Extend mode to connect clients up to 250 meters away by limiting the port speed to 10 Mbps.

Exceptional Built-Quality for Stable Operation

Build Robust Systems with Outstanding EMC

Improves service reliability and reduces downtime caused by power surges and ESD.

ESD: Contact 6kV; Air 8kV
Surge: Power DM 2kV, CM 4kV; RJ45 CM 4kV

Shielded Ports. Solid Metal Casing.
Ensures stable operation with Ethernet ports shielded with nickel-plated cooper alloy and robust SPCC metal casing.

Versatile Scenarios

Surveillance
Office Networking
Campuses Wi-Fi
Accesses and Signages

Techninė specifikacija

Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Gigabit Ethernet (copper) ports quantity	2
Uplink ports quantity	2
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3x, IEEE 802.3z, IEEE 802.3u, IEEE 802.3i, IEEE 802.3ab
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T

Cable types supported	Cat3, Cat4, Cat5, Cat5e
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Ethernet LAN data rates	10,100 Mbit/s
VLAN support	Yes
Data transmission	
MAC address table	2048 entries
Switching capacity	5.6 Gbit/s
Forwarding rate	4.166 Mpps
Store-and-forward	Yes
Packet buffer memory	0.25 MB
Design	
Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, PoE, Power
Performance	
Plug and Play	Yes
Fanless	Yes
Mean time between failures (MTBF)	50000 h
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (typical)	5 W
Power consumption (max)	120 W
Surge protection	Yes
Surge protection voltage	4 kV
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	8
Power over Ethernet plus (PoE+) ports quantity	1
Power over Ethernet (PoE) power per port	30 W

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Total Power over Ethernet (PoE) budget	120 W
Other features	
Warranty period	1 year(s)
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	220 mm
Depth	150 mm
Height	44 mm
Weight	636 g
Packaging content	
Cables included	AC
Packaging data	
Package width	249 mm
Package depth	207 mm
Package height	60 mm
Package weight	1.04 kg
Technical details	
Products per shipping (inner) case	16 pc(s)
Logistics data	
Country of origin	China
Matmenys ir svoris	
Matmenys (I × P × A)	25.00cm × 6.00cm × 21.00cm
Svoris	1.20kg

Dokumentai ir vaizdo įrašai

- User manual
- Product leaflet
- Declaration of conformity

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Gamintojo ir saugos informacija

MANUFACTURER

Cudy

DISTRIBUTOR

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

› Declaration of conformity