

Emergency power supply Armac UPS OFFICE LINE-INTERACTIVE O/650F/LCD

Gamintojas: **ARMAC** · Modelis: **O/650F/LCD** · EAN: **5901969406627** · Prekės kodas: **621556**



68,90 €

Kaina su PVM

Be PVM: **56,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Power protection features: Short circuit | Power protection features: Over power | Power protection features: Input fuse | Depth: 305 mm | Typical backup time at full load: 3 min | Power protection features: Overvoltage protection | Automatic battery test: Yes | Operating relative humidity (H-H): 10 - 90% | Battery voltage: 12 V | Form factor: Tower | Built-in display: LCD | Cold start: Yes | USB port: Yes | Power protection features: Battery discharge | Typical backup time at half load: 20 min | Input frequency: 45 - 65 Hz | AC outlets quantity: 2 AC outlet(s) | Output frequency: 50 Hz | Height: 141 mm | Input operation voltage (min): 145 V | Input operation voltage (max): 290 V | Noise level: 45 dB | Automatic Voltage Regulation (AVR): Yes | Battery technology: Maintenance Free, Lead Acid (AGM) | Output operation voltage (min): 255 V | Output power: 390 W | Weight: 4.6 g | Output operation voltage (max): 195 V | Response time: 2 - 6 ms | Battery capacity: 7 Ah | AC outlet types: Type F | Number of batteries supported: 1 | RJ-45 ports quantity: 2 | Product colour: Black | Battery recharge time (90%): 6 h | UPS topology: Line-Interactive | Output power capacity: 650 VA | Auto-restart: Yes | Waveform: Sine | Width: 85 mm | Operating temperature (T-T): 0 - 45 °C | USB cable included: No | Output voltage: 230 V

Techninė specifikacija

Specifications

Sandėlio grupė

UPS power supplies [+114][-159]

Matmenys ir svoris

Matmenys (I × P × A)	22,00cm × 14,00cm × 37,00cm
Svoris	5,07kg