

TP-Link Omada EAP603-Outdoor 1800 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **EAP603-Outdoor** · EAN: **1210002605731** · Prekės kodas: **621950**



140,90 €

Kaina su PVM

Be PVM: **116,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Seamless 1.8Gbps Wi-Fi 6 Speeds: 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz.†
- ✓ Dual-Band Omnidirectional Coverage: Up to 300 m (984 ft) long-range coverage.*
- ✓ PoE+ Powered: Supports both 802.3at PoE and Passive PoE (adapter included)
- ✓ Ideal for Outdoor Environments: IP65 weatherproof, 6 kV lightning protection, and a reliable operating range of -40 °C to +70 °C
- ✓ Easy and Quick Setup: Wall/pole mounting; Omada SDN for one-click setup
- ✓ Advanced Features: Omada Mesh, Seamless Roaming, and Centralized Cloud Management.§



Aprašymas

TP-Link Omada EAP603-Outdoor. 2,4 GHz, 5 GHz, Maximale Datenübertragungsrate: 1800 Mbit/s. Unterstützte Sicherheitsalgorithmen: EAP, EAP-FAST, EAP-GTC, EAP-MD5, EAP-PEAP, EAP-SIM, EAP-TLS, EAP-TTLS, PEAP, PPSK, SNMP, SSH,.... Ethernet LAN Datentransferraten: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Produktfarbe: Weiß. Stromverbrauch (max.): 4,8 W

Techninė specifikacija

Specifications

Sandėlio grupė	Accesspoints [+292][-30]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	1800 Mbit/s
Maximum data transfer rate (2.4 GHz)	573 Mbit/s
Maximum data transfer rate (5 GHz)	1201 Mbit/s
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11k, IEEE 802.11n, IEEE 802.11r, IEEE 802.11v, IEEE 802.3at
Bluetooth	Yes
Maximum outdoor range	300 m
Security	
Security algorithms	EAP, EAP-FAST, EAP-GTC, EAP-MD5, EAP-PEAP, EAP-SIM, EAP-TLS, EAP-TTLS, PEAP, PPSK, SNMP, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal
MAC address filtering	Yes
IP address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	16
Guest access	Yes
Remote Authentication Dial-In User Service (RADIUS)	Yes
Access Control List (ACL)	Yes
Management features	
Web-based management	Yes
Cloud-managed	Yes
Backup function	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Power	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	Passive PoE
DC voltage range	42.5 - 57 V
Input current	0.36 A

Power consumption (max)	4.8 W
-------------------------	-------

Design

Placement	Pole, Wall
-----------	------------

Product colour	White
----------------	-------

International Protection (IP) code	IP65, IP66
------------------------------------	------------

Antenna

Antenna type	Internal & external
--------------	---------------------

Antenna direction type	Omni-directional
------------------------	------------------

Antennas quantity	4
-------------------	---

Antenna gain level (max)	5 dBi
--------------------------	-------

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
-------------------------	---

Weight & dimensions

Width	230 mm
-------	--------

Depth	207.5 mm
-------	----------

Height	69.7 mm
--------	---------

Packaging content

PoE adapter included	Yes
----------------------	-----

Mounting kit	Yes
--------------	-----

Quick start guide	Yes
-------------------	-----

Operational conditions

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Operating temperature (T-T)	-30 - 70 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Matmenys ir svoris

Matmenys (I × P × A)	22,00cm × 22,00cm × 7,00cm
----------------------	----------------------------

Svoris	0,93kg
--------	--------