

TP-Link Omada 28-Port Gigabit Smart Switch with 24-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **TL-SG2428P** · EAN: **1210002611848** · Prekės kodas: **622950**



329,89 €

Kaina su PVM

Be PVM: **272,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | IP-MAC-Port binding: Yes | Rack mount kit: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Switch layer: L2/L2+ | System event log: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | ARP inspection: Yes | Access Control List (ACL): Yes | BPDU filtering/protection: Yes | Forwarding rate: 41.7 Mpps | Power over Ethernet plus (PoE+) ports quantity: 24 | Authentication type: RADIUS | Switch type: Managed | SSH/SSL support: Yes | Fiber ethernet cabling technology: 1000BASE-X | Queue scheduling algorithms: SP | MIB support: Y | Queue scheduling algorithms: WRR+SP | Virtual LAN features: MAC address-based VLAN | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Cable types supported: Cat4 | Rate limiting: Yes | Virtual LAN features: Protocol-based VLAN | Number of queues: 8 | Broadcast storm control: Yes | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 24 | Virtual LAN features: Voice VLAN | Spanning tree protocol: Yes | Jumbo frames: 9000 | Networking standards: IEEE 802.1Q | Width: 440 mm | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | IGMP snooping: Yes | Networking standards: IEEE 802.1w | Security algorithms: SSH-2 | Networking standards: IEEE 802.3x | Number of VLANs: 4000 | Security algorithms: SSH | Harmonized System (HS) code: 85176990 | Security algorithms: SSL/TLS | DHCP features: DHCP server | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): Yes | AC input frequency: 50/60 Hz | Product colour: Black | Power over Ethernet (PoE) power per port: 30 W | AC input voltage: 100 - 240 V | Form factor: 1U | Power source: AC | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Operating relative humidity (H-H): 10 - 90% | Package depth: 528 mm | Power supply included: Yes | Networking standards: IEEE 802.3i | MAC address table: 8000 entries | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | DHCP features: DHCPv6 client | Networking standards: IEEE 802.1x | Storage relative humidity (H-H): 5 - 90% | Heat dissipation: 1047.3 BTU/h | Firmware upgradeable: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | User guide: Yes | DHCP features: DHCP snooping | Web-based management: Yes | Security algorithms: HTTPS | Package width: 336 mm | 10G support: No | Package weight: 3.98 kg | Cables included: AC | Height: 44 mm | Rack mounting: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | SFP module slots quantity: 4 | Power consumption (max): 306.9 W | Switching capacity: 56 Gbit/s | Networking standards: IEEE 802.1D | Networking standards: IEEE

802.3z | DHCP features: DHCP client | DHCP features: DHCP relay | Number of fans: 2 fan(s) | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Copper ethernet cabling technology: 1000BASE-T | Package height: 100 mm | Depth: 220 mm | Multicast support: Yes | Operating temperature (T-T): 0 - 50 °C | Jumbo frames support: Yes | Total Power over Ethernet (PoE) budget: 250 W | Basic switching RJ-45 Ethernet ports quantity: 24 | VLAN support: Yes | Copper ethernet cabling technology: 10BASE-T

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+91][-88]
Matmenys ir svoris	
Matmenys (I × P × A)	10,00cm × 34,00cm × 54,00cm
Svoris	4,80kg