

TP-Link Omada 28-Port Gigabit L2+ Managed Switch with 24-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **TL-SG3428MP** · EAN: **1210002611909** · Prekės kodas: **622951**



409,90 €

Kaina su PVM

Be PVM: **338,76 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | Active link detection: Yes | Head-of-line (HOL) blocking: Yes | GARP VLAN Registration Protocol (GVRP): Yes | ARP inspection: Yes | Cloud-managed: Yes | Power over Ethernet (PoE): Yes | IGMP snooping: Yes | Width: 440 mm | Harmonized System (HS) code: 85176990 | Rack mounting: Yes | Total Power over Ethernet (PoE) budget: 384 W | Operating temperature (T-T): 0 - 45 °C | User guide: Yes | SSH/SSL support: Yes | Package depth: 528 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Flow control support: Yes | System event log: Yes | Package width: 440 mm | IP-MAC-Port binding: Yes | Switch layer: L2+ | DHCP features: DHCPv6 snooping | Form factor: 1U | Loop protection: Yes | DHCP features: DHCP server | Switching capacity: 56 Gbit/s | Power consumption (max): 463.8 W | SFP module slots quantity: 4 | DHCP features: DHCPv6 client | Management protocols: SNMPv1/v2c/v3, LLDP/LLDP-MED | BPDU filtering/protection: Yes | Static port security: Yes | Package weight: 6.08 kg | Power supply included: Yes | Height: 44 mm | Authentication: MAC-based authentication, Port-based authentication | DHCP features: DHCP snooping | DHCP features: DHCP client | DHCP features: DHCP relay | Number of VLANs: 4000 | Storage relative humidity (H-H): 5 - 90% | Switch type: Managed | Operating relative humidity (H-H): 10 - 90% | Virtual LAN features: Private VLAN | Virtual LAN features: Tagged VLAN | Depth: 330 mm | Multicast support: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Web-based management: Yes | Copper ethernet cabling technology: 10BASE-T | Gigabit Ethernet (copper) ports quantity: 24 | Copper ethernet cabling technology: 1000BASE-T | Access Control List (ACL): Yes | Jumbo frames support: Yes | Link aggregation: Yes | Broadcast storm control: Yes | Number of fans: 2 fan(s) | Store-and-forward: Yes | Virtual LAN features: Port-based VLAN | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 41.66 Mpps | Virtual LAN features: MAC address-based VLAN | VLAN support: Yes | 10G support: No | IP routing: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Configuring Location Settings (CLI): Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Packet buffer memory: 12 MB | Port mirroring: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | AC input voltage: 100 - 240 V | Product colour: Black | LED indicators: Yes | MAC address table: 16000 entries | Console port: RJ-45/micro-USB | AC

input frequency: 50/60 Hz | Virtual LAN features: Voice VLAN | Networking standards: IEEE 802.3af | MAC address filtering: Yes | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3ab | Security algorithms: SSL/TLS | Quick start guide: Yes | Networking standards: IEEE 802.3z | Package height: 100 mm | Rate limiting: Yes | Power source: AC | Security algorithms: SSH

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+91][-88]
Matmenys ir svoris	
Matmenys (I × P × A)	11,00cm × 54,00cm × 47,00cm
Svoris	6,88kg