

Canon EOS R8

Gamintojas: **CANON** · Modelis: **5803C003** · EAN: **4549292204841** · Prekės kodas: **624856**



1 279,90 €

Kaina su PVM

Be PVM: **1 057,77 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ MILC 24.2 MP CMOS Touchscreen Black
- ✓ TTL Face tracking
- ✓ ISO sensitivity (min): 50 ISO sensitivity (max): 204800 Fastest camera shutter speed: 1/16000 s Slowest camera shutter speed: 30 s ± 3EV (1/2EV; 1/3EV step)
- ✓ Video recording 3840 x 2160 pixels 4K Ultra HD
- ✓ Built-in microphone Built-in speaker(s) USB Type-C HDMI Bluetooth Wi-Fi
- ✓ Lithium-Ion (Li-Ion)



Aprašymas

Canon EOS R8. Kamera-Typ: MILC, Megapixel (ca.): 24,2 MP, Sensor-Typ: CMOS, Maximale Bildauflösung: 6000 x 4000 Pixel. ISO-Empfindlichkeit (max): 204800. Kürzeste Verschlusszeit: 1/16000 s. WLAN. HD-Typ: 4K Ultra HD, Maximale Video-Auflösung: 3840 x 2160 Pixel. Touchscreen. Suchertyp: Elektronisch. Gewicht: 414 g. Produktfarbe: Schwarz

Techninė specifikacija

Specifications

Sandėlio grupė

Digitalkameras [+193][-10]

Picture quality

Camera type	MILC
Megapixel (approx.)	24.2 MP
Sensor type	CMOS
Maximum image resolution	6000 x 4000 pixels
Still image resolution(s)	6000 x 4000, 3984 x 2656, 2976 x 1984, 2400 x 1600, 5328 x 4000, 3552 x 2664, 2656 x 1992, 2112 x 1600, 4000 x 4000, 2656 x 2656, 1984 x 1984, 1600 x 1600
Image stabilizer	No
Image formats supported	JPEG, Raw, C-Raw, HEIF
Image sensor aspect ratio	3:2
Sensor cleaning system	Ultrasonic vibration
Sensor cleaning system name	EOS Integrated Cleaning System
Supported aspect ratios	1:1, 3:2, 4:3, 16:9
Image sensor size (W x H)	35.9 x 23.9 mm
Sensor format	Full-frame
Built-in low-pass filter	Yes

Lens system

Lens mount interface	Canon RF
----------------------	----------

Focusing

Focus	TTL
Focus adjustment	Auto/Manual
Auto focusing (AF) modes	Continuous Auto Focus, One Shot Focus, Servo Auto Focus
Auto Focus (AF) object detection	Aircraft, Animal, Bird, Body, CAT, Dog, Eye, Face, Head, Horse, People, Train, Vehicle
Face tracking	Yes
Auto Focus (AF) lock	Yes
Auto Focus (AF) assist beam	Yes

Exposure

ISO sensitivity (min)	50
ISO sensitivity (max)	204800
Light exposure modes	Aperture priority AE, Auto, Manual, Shutter priority AE
Light exposure correction	± 3EV (1/2EV; 1/3EV step)
Light metering	Centre-weighted, Evaluative (Multi-pattern), Spot
ISO sensitivity	100, 200, 400, 800, 1600, 3200, 6400, 12800, 25600, 51200, 102400, Auto
Light exposure control	Program AE
Auto Exposure (AE) lock	Yes

Number of measurement zones	384
Shutter	
Fastest camera shutter speed	1/16000 s
Slowest camera shutter speed	30 s
Camera shutter type	Electronic
Flash	
Flash exposure lock	Yes
External flash connector	Yes
Flash exposure compensation	Yes
Flash exposure correction	±3EV (1/3 EV step)
Shoe mounting point	Yes
Shoe mounting point type	Hot shoe
Video	
Video recording	Yes
Maximum video resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Video resolutions	1920 x 1080,3840 x 2160 pixels
Video formats supported	H.264, H.265
Colour sampling	YCbCr4:2:0 8-bit, YCbCr4:2:2 10-bit
Audio	
Built-in microphone	Yes
Built-in speaker(s)	Yes
Audio system	stereo
Wind filter	Yes
Audio formats supported	LPCM, AAC
Memory	
Compatible memory cards	SD, SDHC, SDXC
Memory slots	1
Display	
Display	LCD
Touchscreen	Yes
Display diagonal (metric)	7.5 cm
Display resolution	1620000 dot
Display aspect ratio	3:2

Vari-angle LCD display	Yes
Viewfinder	
Viewfinder type	Electronic
Magnification	0.7x
Viewfinder screen size	0.39"
Viewfinder frame rate (power saving mode)	60 fps
Viewfinder frame rate (smooth mode)	120 fps
Viewfinder resolution (approx.)	2360000 pixels
Ports & interfaces	
USB version	3.2 Gen 2 (3.1 Gen 2)
HDMI	Yes
USB connector	USB Type-C
HDMI connector type	Micro
Microphone in	Yes
Headphone outputs	1
Headphone connectivity	3.5 mm
Network	
Bluetooth	Yes
Wi-Fi	Yes
Bluetooth version	4.2
Bluetooth Low Energy (BLE)	Yes
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Camera	
White balance	Auto, Cloudy, Custom modes, Daylight, Flash, Fluorescent, Manual, Shade, Tungsten
Scene modes	Children, Close-up (macro), Food, Group photo, HDR backlight control, Handheld night scene, Landscape, Panning, Panorama, Portrait, Self-portrait, Silent shutter, Sports
Shooting modes	Aperture priority, Auto, Flexible priority, Manual, Program, Scene, Shutter priority
Self-timer delay	2,10 s
Tripod mounting supported	Yes
Dioptre correction	Yes
Diopter adjustment (D-D)	-4 - 1
Histogram	Yes
Live view	Yes
Direct printing	Yes
GPS (satellite)	No

Orientation sensor	Yes
Anti-dust function	Yes
Smartphone/tablet remote support	Yes
View on smartphone	Yes
Highlight alert	Yes
Image processor	DIGIC X

Design

Product colour	Black
Dustproof	Yes
Splash proof	Yes

Battery

Battery technology	Lithium-Ion (Li-Ion)
Battery type	LP-E17
Number of batteries supported	1
Battery level indicator	Yes

Power

USB Type-C charging port	Yes
USB Type-C required charging power (min)	7.5 W
USB Type-C required charging power (max)	7.5 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Weight & dimensions

Width	132.5 mm
Depth	70 mm
Height	86.1 mm
Weight	414 g
Weight (including battery)	461 g

Packaging data

Quantity per pack	1 pc(s)
Package width	192 mm
Package depth	282 mm
Package height	153 mm
Package weight	1.16 kg

Packaging content

AC adapter included	Yes
---------------------	-----

Neck strap included	Yes
---------------------	-----

Battery charger included	Yes
--------------------------	-----

Batteries included	Yes
--------------------	-----

Logistics data

Products per pallet	72 pc(s)
---------------------	----------

Matmenys ir svoris

Matmenys (l × p × A)	10,00cm × 17,00cm × 13,00cm
----------------------	-----------------------------

Svoris	0,69kg
--------	--------