

Zyxel XGS1250-12 Managed L2 10G Ethernet (100/1000/10000) Grey

Gamintojas: ZYXEL · Modelis: XGS1250-12-ZZ0102F · EAN: 4718937634453 · Prekės kodas: 625237



226,90 €

Kaina su PVM

Be PVM: 187,52 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2 Web-based management
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 11
- ✓ 10G support
- ✓ MAC address table: 16000 entries Switching capacity: 96 Gbit/s
- ✓ AC Power supply included



Aprašymas

Double the 10G Capability!

XS1250-12 features with three Multi-Gigabit ports supporting up to 10G and one additional 10G fiber port on top of the two 10G copper ports provided by the other vendors. With our additional fiber port and 10G connectivity boost the flexibility to adopt more 10G devices in your daily work.

Agile Network Applications

Featured with 1G ports, 10G Multi-Gigabit ports, as well as 10G fiber port, this port combination is capable of servicing a range of network devices such as iMac Pro, 10G NAS, servers, WiFi 6 APs, or new 2.5G motherboards. The unique 5-color LED on the front panel is designed for you to check the link speed instantly.

Why Multi-Gigabit?

Increasing new applications raise the demand for higher network speed requirement. The Multi-Gigabit RJ-45 ports provide more speed options for

your network. Before upgrading the network, you should figure out network speed of motherboard, PC, or WiFi 6 AP, and you need to pick up the right network cable to achieve the maximum speed.

Using Your Current Cabling Is Fine!

The Multi-Gigabit support is able to leverage existing Cat 5e cable infrastructure to upgrade network speed up to 5 times for cost efficient network setup.

Whisper-silent, Energy-saving at Work

With the built-in smart fan which is designed to automatically adjust speeds based on the device temperature, you can barely hear the sound while the switch is in operation. Also, you can deactivate the Ethernet port LEDs for distraction-free operation by switching to LED ECO mode through the front panel button* or the web-based interface.

Techninė specifikacija

Specifications	
Sandėlio grupė	[NES] NETWORK SWITCHES [+62][-383]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
MIB support	Y
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	11
Basic switching RJ-45 Ethernet ports type	10G Ethernet (100/1000/10000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
SFP+ module slots quantity	1
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	Yes
Port mirroring	Yes
Full duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes

Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000,2500,10000 Mbit/s
VLAN support	Yes
Data transmission	
MAC address table	16000 entries
Switching capacity	96 Gbit/s
Forwarding rate	71.42 Mpps
Jumbo frames support	Yes
Jumbo frames	12000
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	No
Stackable	No
Product colour	Grey
Housing material	Aluminium, Iron
Reset button	Yes
LED indicators	Yes
Redundant fans support	Yes
Wall mountable	Yes
DIN rail mounting	No
Number of fans	1 fan(s)
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	20.06 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	250 mm
Depth	104 mm
Height	27 mm
Weight	783 g
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (I × P × A)	31,00cm × 23,00cm × 7,00cm
Svoris	1,35kg