

Canon imageFORMULA R10 Portable Duplex Document Scanner

Gamintojas: **CANON** · Modelis: **4861C003** · EAN: **4528472109831** · Prekės kodas: **626432**



319,90 €

Kaina su PVM

Be PVM: **264,38 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Scanner type: Sheet-fed scanner 600 x 600 DPI
- ✓ Colour scanning Duplex scanning
- ✓ A4
- ✓ Maximum scan size: 216 x 356 mm Sensor type: CMOS CIS
- ✓ USB port
- ✓ Power supply type: USB 2.5 W

Aprašymas

Canon imageFORMULA R10. Maximale Scan-Abmessung: 216 x 356 mm, Optische Scan-Auflösung: 600 x 600 DPI. Scanner-Typ: Scanner mit Vorlageneinzug, Produktfarbe: Weiß. Sensor-Typ: CMOS CIS, Tägliche Einschaltdauer (max): 500 Seiten, Lichtquelle: RGB-LED. Maximale Papiergröße der ISO A-Serie: A4, Media Dicke (min): 0,08 mm, Kartenstärke (max.): 1,4 mm. Netzteiltyp: USB, Stromverbrauch (Standardbetrieb): 2,5 W, Stromverbrauch (PowerSave): 1,5 W

Techninė specifikacija

Specifications

Sandėlio grupė Scanner [+637][41]

Scanning

Maximum scan size	216 x 356 mm
Optical scanning resolution	600 x 600 DPI
Duplex scanning	Yes
Colour scanning	Yes

Design

Scanner type	Sheet-fed scanner
Built-in display	No
Product colour	White
Performance	
Sensor type	CMOS CIS
Daily duty cycle (max)	500 pages
Light source	RGB LED
Paper handling	
Maximum ISO A-series paper size	A4
Legal	Yes
Media thickness (min)	0.08 mm
Card thickness (max)	1.4 mm
Paper tray media weight	64 - 128 g/m ²
Maximum scan width	21.6 cm
Maximum scan length	35.6 cm
Ports & interfaces	
USB port	Yes
USB version	2
Power	
Power supply type	USB
Power consumption (typical)	2.5 W
Power consumption (PowerSave)	1.5 W
Weight & dimensions	
Width	285 mm
Depth	95 mm
Height	40 mm
Weight	900 g
Packaging data	
Quantity per pack	1 pc(s)
System requirements	
Windows operating systems supported	Windows 10, Windows 10 x64, Windows 8.1, Windows 8.1 x64
Mac operating systems supported	Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina
Operational conditions	

Operating temperature (T-T)	10 - 32.5 °C
Operating relative humidity (H-H)	20 - 80%
Other features	
Warranty period	3 year(s)
Logistics data	
Country of origin	Japan
Harmonized System (HS) code	84716070
Matmenys ir svoris	
Svoris	1,48kg