

CLUB3D USB Gen2 Type-C PD Charging Hub to 2x Type-C 10G ports and 2x USB Type-A 10G ports

Gamintojas: **CLUB 3D** · Modelis: **CSV-1543** · EAN: **8719214472061** · Prekės kodas: **626868**



70,91 €

Kaina su PVM

Be PVM: **58,60 €**

Neturime



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Host interface: USB 3.2 Gen 2 (3.1 Gen 2) Type-C
- ✓ Hub interfaces: USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
- ✓ Ports quantity: 4
- ✓ 10000 Mbit/s
- ✓ USB Power Delivery (USB PD)
- ✓ Black, Silver



Aprašymas

The Club 3D CSV-1543 is an USB Gen2 Type-C PD Charging Hub to 2x Type-C 10G ports and 2x USB Type-A 10G ports. The two USB Type-A ports are designed for transmitting data and one of the two USB Type-A ports can provide 1.5A charging for the connected USB Type-A devices (mobile phones, tablets, U-disk, etc). One of the two USB Type-C ports is designed for transmitting data and charging for the connected USB Type-C device, the other USB Type-C port supports both data and PD3.0 charging. It can work on any USB Type-C host (PC, notebook, tablet, Mobile phone, etc) that supports Power Delivery 3.0.

High Power Conversion Efficiency means low power consumption and low heating 98.2% @Vin=5V; 92.5% @Vin=20V.

Advanced Power Management. The output power will guarantee uninterrupted working of USB Type-A SSD and U Disk when the Vin is in 5; 20V, so the connected USB device will not get disconnected while plugging in and out the PD Charger from the USB Type-C charging port.

Supported USB device current is as follows: 1.5A @PD3.0 device

Note:

1) When the current of the connected USB device is higher than the above listed current, the USB device will get disconnected while plugging the PD Charger and reconnect in a few seconds

2) When working on PD 2.0 supported host PC, the connected USB Type-A device will get disconnected while plugging out the USB Type-C PD Charger and then reconnect in a few seconds

Support Fast Role Swap of PD 3.0 the connected device will not get disconnected while plugging in and out PD Charger when working on PD 3.0 device

Techninė specifikacija

Ports & interfaces	
Ports quantity	4
Host interface	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
Hub interfaces	USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2
Card reader integrated	No
DC-in jack	No
Features	
Data transfer rate	10000 Mbit/s
Product colour	Black, Silver
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	100 W
Cable type	Round cable
Cable length	0.254 m
Plug and Play	Yes
Certification	ROHS, FCC, CE EMI
Power	
Power supply type	USB
Output voltage	5 - 20 V
Output current	1.5 A
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Weight & dimensions	

Width	85 mm
Depth	45 mm
Height	12 mm
Weight	60 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	70 mm
Package depth	35 mm
Package height	320 mm
Package weight	105 g
Package type	Box
Packaging composition	
Plastic packaging weight	3 g
Paper/cardboard packaging weight	42 g
Total plastic packaging weight	0 g
Total paper/cardboard packaging weight	0 g
Logistics data	
Harmonized System (HS) code	84733020