

Asrock PRO-M750G 750W 80 PLUS Gold power supply unit

Gamintojas: **ASROCK** · Modelis: **PRO-M750G** · EAN: **4711581493001** · Prekės kodas: **627904**



94,90 €

Kaina su PVM

Be PVM: **78,43 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt



Aprašymas

Max output current (+12V): 62.5 A | Max output current (+3.3V): 20 A | Product colour: Black | Power supply unit (PSU) form factor: ATX | Power protection features: OPP | Power protection features: SCP | Power protection features: UVP | Power protection features: OCP | Depth: 150 mm | Cooling type: Active | Power protection features: OTP | Combined power (-12V): 3.6 W | Peripheral (Molex) power connectors (4-pin): 4 | Combined power (+5V): 120 W | Height: 86 mm | Power protection features: SIP | Total power: 750 W | Power protection features: OVP | Width: 150 mm | Max output current (+5Vsb): 3 A | PCI Express power connectors (6+2 pin): 3 | Fan diameter: 13.5 cm | Purpose: PC | AC input frequency: 50/60 Hz | Max output current (-12V): 0.3 A | Motherboard power cable length: 60 cm | ATX version: 3.1 | AC input voltage: 100 - 240 V | Input current: 10 - 5 A | Combined power (+3.3V): 120 W | Number of fans: 1 fan(s) | 80 PLUS certification: 80 PLUS Gold | Combined power (+12V): 750 W | Number of SATA power connectors: 4 | Motherboard power connector: 24-pin ATX | Mean time between failures (MTBF): 100000 h | Max output current (+5V): 20 A | CPU power connector (4+4 pin): Yes | Combined power (+5Vsb): 15 W | EPS power connector (4+4 pin): Yes | PCI Express power connectors (12+4 pin): 1

Techninė specifikacija

Specifications

Sandėlio grupė

Power supplies for enclosures [+145][-86]

Matmenys ir svoris

Matmenys (l × P × A)

20,00cm × 30,00cm × 13,00cm

Svoris

2,60kg