

LG 86UH5Q-E Signage Display Digital signage flat panel 2.18 m (86") Wi-Fi 700 cd/m² 4K Ultra HD Black WebOS 24/7

Gamintojas: **LG** · Modelis: **86UH5Q-E.AEU** · EAN: **8806096688731** · Prekės kodas: **629428**



4 381,89 €

Kaina su PVM

Be PVM: **3 621,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Resolution : 3,840 × 2,160 (UHD)
- ✓ Brightness : 500 nits (Typ.)
- ✓ Bezel Width : 13.4 mm (Even)
- ✓ webOS Smart Platform
- ✓ LG Shield



Aprašymas

Superb Picture Quality with Ultra HD Resolution

With the resolution of UHD, it makes the colors and details of the content vivid and realistic. In addition, the wide viewing angle provides clear content.

Convenient webOS Platform

The UH5Q is equipped with a high-performance SoC that allows for multiple tasks to be performed without a separate media player. The webOS platform provides app development tools with an intuitive UI that enhances user convenience, and includes webOS partner apps to create an SI-friendly environment.

Durability that Provides Reliability

Optimized for business environments, the UH5Q is protected against salt, dust, iron powder and humidity thanks to conformal partial coating on

power board, allowing for stable operation. Also, its customer-centric features, such as IP5x and Shock Monitoring*, provide both reliability and satisfaction.

Comprehensive Security

webOS Signage goes beyond security measures at the operating system (OS) level. LG Shield employs a five-tiered defense system, encompassing server, application, operating system, system, and hardware. Each layer operates independently, providing comprehensive protection against various threats. Also, the webOS platform supports ETSI EN 303 645.

SuperSign Solutions

SuperSign is an integrated and intuitive content management solution for creative and organized digital signage content in your space, connecting customers to a range of services with convenient user experiences. There are a variety of versions such as SuperSign Cloud, so discover and enjoy the version that best fits you.

Techninė specifikacija

Specifications	
Sandėlio grupė	Digital Signage [+28][-175]
Display	
Display diagonal	2.18 m (86")
Display resolution	3840 x 2160 pixels
Display brightness	700 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	ADS
LED backlight	Yes
LED backlighting type	Edge-LED
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	1000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Rated lifetime	50000 h
Native refresh rate	60 Hz
Haze rate	25%
Ports & interfaces	
HDMI ports quantity	3
DisplayPorts quantity	1

USB port	Yes
HDMI version	2.2/1.4
HDMI input ports quantity	3
USB ports quantity	2
USB version	2
USB connector type	Mini-USB A
Ethernet LAN (RJ-45) ports	1
RS-232C	Yes
Remote (IR) input	1
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor/outdoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Screen shape	Flat
Panel mounting interface	600 x 400 mm
Performance	
Purpose	Commercial
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	English, French, German, Spanish, Italian, Korean, Simplified Chinese, Traditional Chinese, Portuguese, Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Dutch, Czech, Greek, Turkish, Arabic
Operating hours (hours/days)	24/7
HDCP	Yes
International Protection (IP) code	IP5X
Screen sharing	Yes
webRTC support	Yes
Power	
Power consumption (typical)	205 W
Power consumption (off)	0.5 W

Power consumption (max)	297 W
AC input voltage	100-240 V
AC input frequency	50/60 Hz
Heat generation (typical)	699 BTU/h
Heat generation (max)	1013 BTU/h
Computer system	
Internal memory	16 GB
Operating system installed	WebOS
Operating system version	8
Weight & dimensions	
Display width	1928.8 mm
Display depth	29.7 mm
Display height	1099.8 mm
Display weight	53 kg
Packaging data	
Package width	2100 mm
Package depth	253 mm
Package height	1250 mm
Package weight	66.7 kg
Packaging content	
Remote control included	Yes
Cables included	Power
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Sensors	
Gyroscope	Yes
Temperature sensor	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Features	
Wall mountable	Yes
Matmenys ir svoris	

Matmenys (I × P × A)	10,00cm × 10,00cm × 10,00cm
Svoris	64,00kg