

TP-Link Omada AX3000 Indoor/Outdoor WiFi 6 Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP650-Outdoor** · EAN: **4897098683552** · Prekės kodas: **629541**



176,90 €

Kaina su PVM

Be PVM: **146,20 €**

Sandėlyje



Prekę internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | Networking standards: IEEE 802.11ax | Security algorithms: WPA | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | 5 GHz: Yes | Maximum data transfer rate: 3000 Mbit/s | Placement: Pole, Wall | Reset button: Yes | Antenna type: Internal | Width: 280.4 mm | 2.4 GHz: Yes | Operating temperature (T-T): -30 - 70 °C | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3at | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Ethernet LAN (RJ-45) ports: 1 | Quick start guide: Yes | International Protection (IP) code: IP67 | Networking standards: IEEE 802.11b | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.1x | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11a | MAC address filtering: Yes | Security algorithms: WPA-Enterprise | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 | Quantity per pack: 1 pc(s) | Mounting kit: Yes | Antenna direction type: Omni-directional | Product colour: White | LED indicators: Yes | Ethernet LAN data rates: 100 Mbit/s | Maximum data transfer rate (5 GHz): 2402 Mbit/s | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Number of users: 250 user(s) | Service Set Identifier (SSID) features: Multiple SSIDs | Fit AP mode features: Mesh networking | VLAN support: Yes | Height: 56.8 mm | Airtime Fairness (ATF): Yes | MIMO type: Multi User MIMO | Maximum data transfer rate (2.4 GHz): 574 Mbit/s | Depth: 106.5 mm | Service Set Identifier (SSID) features: SSID broadcast on/off | Cabling technology: 10/100/1000Base-T(X) | Automatic channel selection: Yes | Rate limiting: Yes | Automatic channel scanning: Yes | Band steering: Yes | 6 GHz: No | BeamForming: Yes

Techninė specifikacija

Specifications

Sandėlio grupė

AccesPoint [+44][-28]

Matmenys ir svoris	
Matmenys (l × p × A)	7,00cm × 32,00cm × 24,00cm
Svoris	1,30kg