

TP-Link 4G+ AX1800 Whole Home Mesh WiFi 6 Gateway

Gamintojas: **TP-LINK** · Modelis: **DECO X20-4G** · EAN: **6935364006709** · Prekės kodas: **629542**



178,90 €

Kaina su PVM

Be PVM: **147,85 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Supported WAN type: Dynamic IP/Static IP/PPPoE/L2TP/PPTP | Certification: CE, RoHS | Harmonized System (HS) code: 85171800 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | UMTS bands supported: 850 | 3G standards: UMTS | 3G standards: DC-HSPA+ | Cloud services supported: TP-Link ID | Built-in processor: Yes | UMTS bands supported: 900 | UMTS bands supported: 2100 MHz | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 | Mobile network generation: 3G, 4G | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 900 | Ethernet cable: Yes | Number of devices supported: 150 | Number of guest networks (5 GHz): 1 | Port forwarding: Yes | Static IP: Yes | 3G standards: HSPA | WLAN data transfer rate (second band): 1201 Mbit/s | 4G standard: TD-LTE & FDD-LTE | WLAN data transfer rate (first band): 574 Mbit/s | Point-to-point protocol over Ethernet (PPPoE): Yes | Dynamic IP: Yes | 4G bands supported: 1800 | AC adapter input current: 0.6 A | Supported network protocols (IPv6): Y | MU-MIMO technology: Yes | Dynamic DNS (DDNS): Yes | Guest access: Yes | Number of guest networks (2.4 GHz): 1 | SIM card type: NanoSIM | Transmit power: CE: ≤20 dBm (2.4GHz), ≤23 dBm (5GHz) | Operating modes: 3G/4G, Router, Access Point | Networking standards: IEEE 802.11a | Security algorithms: WPA-PSK | AC input frequency: 50/60 Hz | AC adapter output current: 1.5 A | Networking standards: IEEE 802.11ax | Product colour: White | AC adapter output voltage: 12 V | DC-in jack: Yes | Antenna type: Internal | Package height: 124 mm | Number of products included: 1 pc(s) | Reset button: Yes | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | AC input voltage: 100 - 240 V | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Warnings: Avoid contact with liquids as this may cause electric shock. | Security algorithms: WPA | Package weight: 1.22 kg | Height: 167 mm | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Ethernet WAN: Yes | Networking standards: IEEE 802.11b | Width: 105 mm | LED indicators: Power | Processor frequency: 1.5 GHz | Networking standards: IEEE 802.11ac | Package width: 241 mm | Package depth: 213.5 mm | Warnings: Do not open the appliance housing - risk of electric shock. | Ethernet LAN (RJ-45) ports: 3 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Number of units included: 1 pc(s) | Processor cores: 4 | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Depth: 105 mm | Wi-Fi standards: 802.11g | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Antennas quantity: 4 | MIMO: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Wi-Fi standards: 802.11b | Quality of Service (QoS) support: Yes |

AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C

Techninė specifikacija

Specifications	
Sandėlio grupė	Routers [+111][-106]
Matmenys ir svoris	
Matmenys (l × p × a)	13,00cm × 24,00cm × 22,00cm
Svoris	1,21kg