

TP-Link LiteWave 8-Port Gigabit Desktop Switch with 8-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **LS108GP** · EAN: **4895252505986** · Prekės kodas: **629543**



51,90 €

Kaina su PVM

Be PVM: 42,89 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Cable types supported: Cat4 | Power supply included: Yes | Switching capacity: 16 Gbit/s | Power over Ethernet plus (PoE+) ports quantity: 8 | Power connector: DC-in jack | Cable types supported: Cat3 | Flow control support: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | DC input voltage: 53.5 V | Forwarding rate: 11.9 Mpps | 10G support: No | Heat dissipation: 243.47 BTU/h | Switch type: Unmanaged | Cable types supported: Cat5 | Cable types supported: Cat5e | Jumbo frames: 16000 | MAC address table: 4000 entries | Basic switching RJ-45 Ethernet ports quantity: 8 | Auto-negotiation: Yes | Power over Ethernet (PoE): Yes | Operating temperature (T-T): 0 - 40 °C | Power source: DC/PoE | Width: 158 mm | Power consumption (max): 71.61 W | AC input voltage: 220 V | Product colour: Black | Total Power over Ethernet (PoE) budget: 62 W | LED indicators: Yes | User guide: Yes | Height: 25 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Input current: 1.31 A | Depth: 99 mm | Auto MDI/MDI-X: Yes | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3z | AC input frequency: 50 Hz | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Power over Ethernet (PoE) power per port: 30 W | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Package type: Box

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+86][-92]

Matmenys ir svoris

Matmenys (I × P × A)	12,00cm × 20,00cm × 13,00cm
----------------------	-----------------------------

Svoris	0,80kg
--------	--------