

ASUS ProArt PA278CGRV computer monitor 68.6 cm (27") 2560 x 1440 pixels Wide Quad HD LCD Silver

Gamintojas: **ASUS** · Modelis: **90LM06Q1-B01K71** · EAN: **4711636229456** · Prekės kodas: **630258**



346,89 €

Kaina su PVM

Be PVM: **286,69 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 27-inch QHD (2560 x 1440) display with 178° wide-view IPS panel
- ✓ Wide 97% DCI-P3 and 100% sRGB gamut to meet international color standards
- ✓ Calman Verified with factory calibrated for excellent Delta E < 2 color accuracy
- ✓ 144Hz variable refresh rate (VRR) with AMD FreeSync, providing creators smooth fast-rendering and comfortable viewing experience
- ✓ Rich connectivity including USB-C up to 96W Power Delivery, HDMI, DisplayPort with daisy-chaining and a built-in USB Hub
- ✓ Model P3 Color Temperature matches the color performance of MacBook display
- ✓ ASUS Light Sync solution with Ambient Light Sensor automatically adjusts the monitor's color gamut based on ambient lighting, for true colors in any environment
- ✓ Built-in Auto KVM allows for effortless switching between two connected laptops or PCs with a single keyboard and mouse
- ✓ Exclusive ASUS DisplayWidget Center application enables easy OSD access and monitor settings adjustments with a mouse
- ✓ Ergonomic design with tilt, swivel, pivot and height adjustments for a comfortable viewing experience

5 YŲ GARANTIJĄ UŽPATVATINANTIS KODAS



*Garantiją keičiantis kodas QR kodas skenuojamas.



Aprašymas

ASUS ProArt Display PA278CGRV Professional Monitor – 27-inch, IPS, 144Hz, QHD (2560 x 1440), 97% DCI-P3, Color Accuracy $\Delta E < 2$, Calman Verified, USB-C PD 96W, Light Sync, Auto KVM, Ergonomic Stand, VESA DisplayHDR 400, ASUS DisplayWidget Center, Green

Sustainability

All the Essentials for Pros

ProArt Display PA278CGRV is a 27-inch IPS QHD monitor tailored for creative professionals. 97% DCI-P3 color gamut, factory calibration to Delta E < 2, and Calman Verified for superb color accuracy. It features a 144 Hz VRR with AMD FreeSync for ultra-smooth visuals and introduces the new M Model color temperature for consistent P3 color on MacBooks. With DisplayPort, HDMI, plus USB-C port offers DisplayPort support and enables superfast data transfers and 96-watt power delivery via a single cable. It ensures seamless connectivity for all your creative needs.

Techninė specifikacija

Specifications	
Sandėlio grupė	Audio, Video, Display & TV - Displays - Business Monitors [+176][-250]
Display	
Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
Native aspect ratio	16:9
Display technology	LCD
Touchscreen	No
HD type	Wide Quad HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1500:1
Maximum refresh rate	144 Hz
Display number of colours	1.073 billion colours
LED backlight	Yes
Display brightness (peak)	400 cd/m²
Display brightness (typical)	350 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Contrast ratio (dynamic)	3000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.233 x 0.233 mm
Pixel density	109 ppi
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Digital horizontal frequency	31 - 223 kHz

Digital vertical frequency	48 - 144 Hz
Display diagonal (metric)	69 cm
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10), DisplayHDR 400
Colour gamut standard	sRGB, DCI-P3
sRGB coverage (typical)	100%
DCI-P3 coverage	97%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	Yes
VESA Adaptive Sync support	Yes
Flicker-free technology	Yes
Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Professional
Product colour	Silver
Detachable stand	Yes
Feet colour	Silver
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of upstream ports	2
Number of downstream ports	4
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	Yes

USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	96 W
HDMI ports quantity	1
HDMI version	2.1
DisplayPorts quantity	2
DisplayPort version	1.4
Headphone outputs	1
Headphone connectivity	3.5 mm
Built-in KVM switch	Yes
HDCP	Yes
HDCP version	1.4
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Cable lock slot type	Kensington
Adjustable height (max)	13 cm
Pivot	Yes
Pivot angle	90 - -90°
Swivelling	Yes
Swivel angle range	30 - -30°
Tilt adjustment	Yes
Tilt angle range	23 - -5°
Power	
Energy efficiency class (SDR)	D
Energy efficiency class (HDR)	G
Energy consumption (SDR) per 1000 hours	17 kWh
Energy consumption (HDR) per 1000 hours	39 kWh
Power consumption (typical)	20 W
Power consumption (PowerSave)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G

Weight & dimensions

Width (with stand)	612.2 mm
Depth (with stand)	190.4 mm
Height (with stand)	536.1 mm
Weight (with stand)	6.6 kg
Width (without stand)	612.2 mm
Depth (without stand)	46.9 mm
Height (without stand)	362.9 mm
Weight (without stand)	4.7 kg

Packaging data

Package width	691 mm
Package depth	140 mm
Package height	427 mm
Package weight	9.4 kg
Package type	Box

Packaging content

Stand included	Yes
----------------	-----

Sustainability

Sustainability certificates	ENERGY STAR, EPEAT Gold, TCO, Forest Stewardship Council (FSC) Mix
-----------------------------	--

Matmenys ir svoris

Matmenys (I × P × A)	69,00cm × 42,00cm × 14,00cm
Svoris	9,40kg