

TP-Link LS1016G network switch Unmanaged Gigabit Ethernet (10/100/1000) Black

Gamintojas: **TP-LINK** · Modelis: **LS1016G** · EAN: **1210002602037** · Prekės kodas: **631927**



63,90 €

Kaina su PVM

Be PVM: **52,81 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 16× 10/100/1000Mbps ports
- ✓ Supports MAC address self-learning, Auto MDI/MDIX and Auto Negotiation
- ✓ Plug & play design
- ✓ QoS ensures smooth traffic for latency sensitive applications such as voice or video
- ✓ Innovative energy-efficient technology saves power consumption
- ✓ Fanless design reduces power consumption and ensures silent operation, ideal for noise-sensitive homes or businesses
- ✓ Durable metal casing provides improved heat dissipation and ensures a longer product life
- ✓ Desktop or rackmount installation



Aprašymas

What This Product Does

The LS1016G Gigabit Ethernet Switch provides you with a high-performance, low-cost, easy-to-use, seamless and standard upgrade to improve old network to 1000Mbps network. All 16 ports support auto MDI/MDIX, no need to worry about the cable type, simply plug and play. Moreover, with the innovative energy-efficient technology, the LS1016G can save power consumption, making it an eco-friendly solution for your business network.

Techninė specifikacija

Specifications

Sandėlio grupė	Switches [+72][(-278)]
----------------	------------------------

Management features

Switch type	Unmanaged
-------------	-----------

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)

Network

Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x
10G support	No
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes

Data transmission

MAC address table	8000 entries
Switching capacity	32 Gbit/s
Forwarding rate	23.808 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	15000

Design

Rack mounting	Yes
Product colour	Black

Performance

Fanless	Yes
---------	-----

Power

Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	0.3 A

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	24.42 BTU/h
Weight & dimensions	
Width	294 mm
Depth	140 mm
Height	44 mm
Packaging content	
Cables included	AC
Rack mount kit	Yes
Certificates	
Certification	FCC, CE, RoHs