

ACT USB 40Gbps M.2 2280 NVMe / PCIe SSD Enclosure, tool-free

 Gamintojas: **ACT** · Modelis: **AC1625** · EAN: **8716065575484** · Prekės kodas: **632370**


87,89 €

Kaina su PVM

 Be PVM: **72,64 €**


Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Tool-free aluminium USB4® 40Gbps enclosure for an M.2 2280 NVMe/PCIe SSD with M key or B+M key
- ✓ Including a USB4® USB Type-C® cable
- ✓ Aluminium design with cooling fins, thermal pad and aluminium strip for better heat dissipation
- ✓ Backwards compatible with USB 3.2, 3.1, 3.0 and USB 2.0
- ✓ USB powered; LED status indicator
- ✓ Comes with a travel clip



Aprašymas

The AC1625 USB4® 40Gbps SSD Enclosure is a high-performance storage solution designed for M.2 2280 NVMe/PCIe SSDs with M key or B+M key. This enclosure features a tool-free, aluminium construction with cooling fins, aluminium strip and thermal pad, providing efficient heat dissipation.

Compatible with M.2 2280 NVMe/PCIe SSDs with M key and B+M key

This SSD enclosure is specifically designed for an M.2 2280 NVMe/PCIe SSDs with M key and B+M key, providing a secure and compatible housing for your drive. Please note that a SATA SSD doesn't fit.

High-Speed USB4® 40Gbps Connectivity

The AC1625 supports the USB4® technology with a maximum speed of 40Gbps. The enclosure supports UASP (USB Attached SCSI-Protocol) and is

backwards compatible with USB 3.2, 3.1, 3.0, and USB 2.0, ensuring seamless connectivity across various devices.

Tool-Free Design and LED Status Indicator

The tool-free design allows for easy installation and removal of your M.2 SSD, while the LED status indicator provides a clear visual indication of the enclosure's activity. A USB4® USB Type-C cable is included, making it easy to connect the enclosure to your device.

Optimal heat dissipation

The AC1625 enclosure includes cooling fins, a thermal pad and aluminium strip to help manage heat. The cooling fins increase the surface area, allowing better heat dissipation, while the thermal pad and aluminium strip facilitates heat transfer from the SSD to the aluminium enclosure. This helps keep the SSD at a stable temperature, reducing the risk of overheating during use.

Techninė specifikacija

Specifications	
Sandėlio grupė	Gehäuse [+3824][-108]
Storage	
Storage drive size	M.2
Supported storage drive interfaces	M.2, PCI Express
Number of storage drives supported	1
Supported storage drive lengths	80 mm
NVMe	Yes
Ports & interfaces	
USB connectivity	Yes
USB version	USB4 Gen 3x2
USB connector type	USB Type-C
USB connector gender	Female
USB ports quantity	1
Design	
Product type	SSD enclosure
Product colour	Grey
Material	Aluminium
Performance	
Data transfer rate	40 Gbit/s
UASP support	Yes
TRIM support	Yes
Power	
Power source type	USB
Weight & dimensions	

Width	118 mm
Depth	50 mm
Height	15 mm
Package width	183 mm
Package depth	50 mm
Package height	133 mm
Package weight	269 g
Packaging content	
Cables included	USB Type-C to USB Type-C
Matmenys ir svoris	
Svoris	0,27kg