

Thermaltake Smart BX1 power supply unit 550 W 24-pin ATX ATX Black

Gamintojas: **THERMALTAKE** · Modelis: **PS-SPD-0550NNSABE-1** · EAN: **4711246875227** · Prekės kodas: **633024**



52,90 €

Kaina su PVM

Be PVM: **43,72 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

EPS version: 2.92 | Cooling type: Active | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 4 | Max output current (+5Vsb): 2.5 A | Safety: CE, CB, TUV, EAC, RCM | Height: 86 mm | Max output current (+12V): 38 A | Maximum input current (@220V): 10 A | Operating relative humidity (H-H): 20 - 85% | Peripheral (Molex) power cable length: 500 mm | Power supply unit (PSU) form factor: ATX | Power Factor Correction (PFC) type: Active | AC input frequency: 50 Hz | Total power: 550 W | Combined power (-12V): 6 W | CPU power cable length: 65 cm | Operating temperature (T-T): 5 - 40 °C | On/off switch: Yes | Fan location: Top | Peripheral (Molex) power cable length: 150 mm | Cabling type: Non-Modular | Illumination: No | Combined power (+12V): 456 W | Storage relative humidity (H-H): 10 - 95% | Combined power (+3.3V): 105 W | Product colour: Black | Floppy disk drive connector: Yes | PCI Express connector: Yes | Max output current (+3.3V): 21 A | Max output current (-12V): 0.5 A | SATA power cable length: 500 mm | Combined power (+5Vsb): 12.5 W | Width: 150 mm | Combined power (+5V): 105 W | AC input voltage: 230 V | Peak power: 660 W | Floppy drive power connector: 1 | Number of SATA power connectors: 6 | Storage temperature (T-T): -40 - 55 °C | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Depth: 140 mm | Hold time: 16 ms | Noise level: 37.6 dB | Max output current (+5V): 16 A | Fan diameter: 12 cm | Motherboard power cable length: 60 cm | CPU power connector (4+4 pin): Yes | Purpose: PC | Input current: 10 A | SATA power cable length: 150 | Efficiency: 88% | ATX version: 2.3 | Motherboard power connector: 24-pin ATX | Power Good signal delay range: 100 - 500 ms | Number of fans: 1 fan(s)

Techninė specifikacija

Specifications

Sandėlio grupė

Power supplies for enclosures [+124][-111]

Matmenys ir svoris

Matmenys (l × P × A)

10,00cm × 25,00cm × 20,00cm

Svoris

1,99kg