

Thermaltake Smart BX3 power supply unit 650 W ATX Black

Gamintojas: THERMALTAKE · Modelis: PS-SPD-0650NNFABE-3 · EAN: 4711475643048 · Prekės kodas: 633027



55,90 €

Kaina su PVM

Be PVM: 46,20 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Max output current (+3.3V): 18 A | Hold time: 150 ms | Combined power (+3.3V): 110 W | Max output current (+12V): 54.2 A | Height: 140 mm | Power supply unit (PSU) form factor: ATX | Max output current (-12V): 0.3 A | 80 PLUS certification: 80 PLUS Bronze | PCI Express power connectors (6+2 pin): 2 | Power Factor Correction (PFC) type: Active | Peripheral (Molex) power cable length: 150 mm | Silent mode: Yes | Number of SATA power connectors: 4 | Max output current (+5V): 18 A | Peripheral (Molex) power cable length: 500 mm | Cabling type: Non-Modular | PCI Express connector: Yes | Combined power (+5Vsb): 15 W | Combined power (+5V): 110 W | Total power: 650 W | Combined power (-12V): 3.6 W | Purpose: PC | Max output current (+5Vsb): 3 A | Peak power: 650 W | CPU P4 connector (4-pin): 2 | Combined power (+12V): 650 W | Fan diameter: 12 cm | ATX version: 3.1 | Width: 150 mm | Depth: 86 mm | Product colour: Black | AC input voltage: 100 - 240 V | Input current: 15 A | Peripheral (Molex) power connectors (4-pin): 4 | ATX Power connector (24-pin): Yes | Warnings: Avoid contact of the product with water or other liquids. | Warnings: The product is not suitable for disposal with municipal waste - dispose of in accordance with local regulations. | AC input frequency: 50/60 Hz | Warnings: Do not open the case - risk of electric shock.

Techninė specifikacija

Specifications

Sandėlio grupė

Power supplies for enclosures [+124][-111]

Matmenys ir svoris

Matmenys (I × P × A)

12,00cm × 28,00cm × 21,00cm

Svoris	2,19kg
--------	--------