

Hikvision HM-TD2628-3/G1/T3A security camera Bullet IP security camera Outdoor 2688 x 1944 pixels Wall

Gamintojas: **HIKVISION** · Modelis: **HM-TD2628-3/G1/T3A** · EAN: **6974004647766** · Prekės kodas: **633201**



556,90 €

Kaina su PVM

Be PVM: **460,25 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

Lens viewing angle, horizontal: 84° | User access level: Administrator, Operator, User | Number of simultaneous live view channels: 20 channels | Lens viewing angle, vertical: 43.1° | IFOV (spatial resolution): 3.33 mRad | B/W night vision distance: 30 m | Thermal sensitivity (NETD): 25 mK | Thermal module: Yes | Effective sensor resolution (thermal module): 256 x 192 pixels | Fixed focal length (thermal module): 3.6 mm | Aperture number (thermal module): 1 | Sensor type (thermal module): Vanadium Oxide Uncooled Focal Plane Arrays | Horizontal field of view (thermal module): 50° | Mounting type: Wall | Power consumption (Power over Ethernet (PoE)): 24 W | Dynamic range: 120 dB | DC output current: 2.5 A | Identify distance (wide): 15 m | Temperature sensor: Yes | Identify distance (tele): 56 m | Password protection: Yes | Video compression formats: H.265 | Closest focusing distance: 0.3 m | Digital zoom: 4x | Temperature measurement range: -20 - 150 °C | Video compression formats: H.264 | Compliance certificates: CB | Compliance certificates: Electromagnetic Compatibility (EMC) | Progressive scan: Yes | Maximum aperture number: 1.6 | Frame rate: 25 fps | Night vision: Yes | Terminal block port: Yes | Alarm input/output: Yes | Day/night mode: Yes | Fixed focal length: 4.3 mm | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: KC | Video compression formats: M-JPEG | Recognize distance (wide): 37 m | Detect distance (wide): 150 m | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: BIS | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: REACH | Placement supported: Outdoor | Audio input: 3.5 mm | Automatic Network Replenishment (ANR): Yes | Built-in HDD: No | Web browser: Yes | Alarm input channels: 2 | Output impedance: 600 Ω | Vertical field of view (thermal module): 37.3° | Languages support: Multi | Live view: Yes | Infrared spectral band: 8 - 14 μm | Maximum memory card size: 512 GB | Recognize distance (tele): 112 m | Sensor type: CMOS | Number of languages: 32 | Audio formats supported: G.711 A-law | IP address filtering: Yes | Audio formats supported: G.711 μ-law | HTTPS encryption: Yes | Audio formats supported: G.726 | Audio formats supported: G.722 | Audio formats supported: PCM | Number of users: 32 user(s) | Audio formats supported: MP2L2 | Detect distance (tele): 460 m | Alarm output channels: 2 | DC output voltage: 12, 24, 42.5, 57 | Product colour: White | Operating relative humidity (H-H): 0 - 95% | Zoom capability: Yes | Power source type: DC, PoE | Ethernet LAN (RJ-45) ports: 1 | Form factor: Bullet | Pixel pitch (thermal module): 12 μm | Minimum illumination: 0 lx | Supported graphics resolutions: 640 x 512 | Width: 113 mm | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 352 x 288 | Maximum resolution: 2688 x 1944 pixels | Ethernet interface type: Fast Ethernet | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 342 x 240 | Web-based management: Yes | Network access storage (NAS): Yes | Type: IP security camera | Bluetooth: No | International Protection (IP) code: IP67 | Number of cameras: 1 | Weight: 1.71 kg | Number of detectable fire points: 10 | Quality of Service (QoS) support: Yes | Power consumption (max): 24 W | Product colour: Black | Wide Dynamic Range (WDR): Yes | Audio input channels: 1.0 channels | Wi-Fi: No |

Temperature measurement accuracy: 8 °C | Compatible memory cards: MicroSDHC | LED type: IR/White | RS-485 ports: 1 | Ethernet LAN: Yes | IK code: IK10 | Supported network protocols: IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP,DNS,DDNS,NTP,RTSP,RTCP,RTP,TCP,UDP,IGMP,ICMP,DHCP,PPPoE,Bonjour,SFTP,SRTP | Length: 349.1 mm | Height: 105 mm | Compatible memory cards: MicroSD (TransFlash) | Total megapixels: 5 MP | Camera shutter speed: 1 - 1/100000 s | Compatible memory cards: MicroSDXC | Night vision distance: 30 m | Card reader integrated: Yes | Operating temperature (T-T): -40 - 65 °C | Connectivity technology: Wired | Fire detection: Yes

Techninė specifikacija

Specifications	
Sandėlio grupė	Video cameras [+121][-119]
Matmenys ir svoris	
Matmenys (I × P × A)	16,00cm × 20,00cm × 40,00cm
Svoris	2,69kg