

ASUS ROG -THOR-1600T3-GAMING-EVO power supply unit 1600 W 20+4 pin ATX ATX Grey

Gamintojas: **ASUS** · Modelis: **90YE00VB-B0NA00** · EAN: **4711636587020** · Prekės kodas: **633570**



731,90 €

Kaina su PVM

Be PVM: **604,88 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1600 W 100 - 240 V
- ✓ Motherboard power connector: 20+4 pin ATX
- ✓ PC ATX 80 PLUS Titanium
- ✓ Active
- ✓ Grey



Aprašymas

Ultimate Power. Unmatched Stability

The ROG Thor 1600W Titanium III EVO delivers the power and stability demanded by gamers. A next-gen GaN MOSFET boosts efficiency, while GPU-First voltage sensing with a patented intelligent stabilizer ensures stable, top-tier performance. Turbo Mode maximizes cooling for overclocking and demanding workloads.

The ROG Thor 1600W Titanium III EVO also includes the ROG Equalizer, a patented 12V-2x6 PCIe power cable engineered to reduce heat stress and keep cable and connector temperatures well to protect the graphics card. With full ATX 3.1 compliance and a native 12V-2x6 connector, the ROG Thor III Titanium Series ensures your high-end rig has the power to conquer any challenge.

The ROG Thor 1600W Titanium III EVO retains its signature OLED display, now with magnetic attachment for easy swapping to either side, supporting both fan-up and fan-down installations. An included Type-C extender further enables flexible relocation to the chassis front or exterior for

maximum visibility.

Patented ROG Equalizer PCIe Cable

Engineered to reduce heat stress and keep cable and connector temperatures well to protect the graphics card.

Techninė specifikacija

Specifications	
Sandėlio grupė	Netzteile [+743][-41]
Power	
Total power	1600 W
AC input voltage	100 - 240 V
Power Factor Correction (PFC) type	Active
Combined power (+3.3V)	125 W
Combined power (+12V)	1600 W
Combined power (+5V)	125 W
Combined power (-12V)	3.6 W
Combined power (+5Vsb)	15 W
Max output current (+3.3V)	30 A
Max output current (+12V)	133.3 A
Max output current (+5V)	25 A
Max output current (-12V)	0.3 A
Max output current (+5Vsb)	3 A
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage
Ports & interfaces	
Motherboard power connector	20+4 pin ATX
Peripheral (Molex) power connectors (4-pin)	3
Motherboard power cable length	61 cm
Number of SATA power connectors	9
Number of SATA power cables	3
PCI Express power connectors (6+2 pin)	3
PCI Express power connectors (16-pin)	2
PCI Express power cable length	75 cm
CPU power connector (4+4 pin)	Yes
CPU power cable length	100 cm
ATX power connector (20+4 pin)	Yes
PCI Express connector	Yes

Cabling type	Fully-Modular
Performance	
Purpose	PC
Power supply unit (PSU) form factor	ATX
80 PLUS certification	80 PLUS Titanium
ATX version	3.1
Bearing technology	DBB
Mean time between failures (MTBF)	120000 h
Design	
Product colour	Grey
Cooling type	Active
Number of fans	1 fan(s)
Illumination	Yes
Built-in display	Yes
Display type	OLED
On/off switch	Yes
Packaging content	
Cables included	CPU, PCIe, Peripheral (Molex), SATA
Cable tie(s) included	Yes
Weight & dimensions	
Width	190 mm
Depth	150 mm
Height	86 mm
Weight	2.5 kg
Packaging data	
Package width	397 mm
Package depth	250 mm
Package height	159 mm
Package weight	5.91 kg
Package type	Box
Logistics data	
Quantity per pack	1 pc(s)
Matmenys ir svoris	
Svoris	6,11kg