

iiyama ProLite XUB2790QSUH-B2 computer monitor 68.6 cm (27") 2560 x 1440 pixels Quad HD LED Black

Gamintojas: IIYAMA · Modelis: XUB2790QSUH-B2 · EAN: 4948570125524 · Prekės kodas: 634053



342,90 €

Kaina su PVM

Be PVM: 283,39 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 68.6 cm (27") LED IPS
- ✓ Quad HD 2560 x 1440 pixels 16:9
- ✓ 100 Hz 0.4 ms 250 cd/m² 1300:1
- ✓ AMD FreeSync Flicker-free technology
- ✓ E 21.4 kWh 26 W



Aprašymas

Ideal for hybrid work and video calls, the 27" ProLite XUB2790QSUH combines sharp QHD resolution and IPS colour accuracy with built-in collaboration tools. The integrated 5MP Windows Hello webcam and microphone make secure logins and virtual meetings effortless. With USB-C (65W PD), HDMI, DisplayPort and a KVM switch, it streamlines multi-device setups while powering your laptop. Flicker-free and blue light reducing technology protect your eyes during long sessions. The ergonomic stand with height, pivot, swivel and tilt ensures all-day comfort. A USB hub, speakers and headphone jack round out this versatile workspace solution.

Techninė specifikacija

Specifications

Sandėlio grupėMonitore [+1517][-101]

Display

Display diagonal	68.6 cm (27")
Display resolution	2560 x 1440 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	No
HD type	Quad HD
Panel type	IPS
Response time	0.4 ms
Screen shape	Flat
Contrast ratio (typical)	1300:1
Maximum refresh rate	100 Hz
Display number of colours	16.7 million colours
Display brightness (typical)	250 cd/m²
Response time (MPRT)	0.4 ms
Display surface	Matt
Contrast ratio (dynamic)	8000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.233 x 0.233 mm
Horizontal scan range	30 - 147 kHz
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Digital horizontal frequency	30 - 147 kHz
Display diagonal (metric)	68.5 cm
DDC/CI	Yes
sRGB coverage (typical)	99%
NTSC coverage (typical)	72%

Performance

AMD FreeSync	Yes
VESA Adaptive Sync support	Yes
Flicker-free technology	Yes
Low Blue Light technology	Yes

Multimedia

Built-in speaker(s)	Yes
Built-in camera	Yes
Number of speakers	2
RMS rated power	4 W
Megapixel (approx.)	5 MP
Built-in microphone	Yes
Design	
Market positioning	Business
Product colour	Black
Frameless design	Yes
Feet colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of upstream ports	1
Number of downstream ports	3
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	2
USB Type-C DisplayPort Alternate Mode	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	65 W
HDMI ports quantity	1
HDMI version	2
DisplayPorts quantity	1
DisplayPort version	1.4
Headphone outputs	1
Built-in KVM switch	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes

Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Adjustable height (max)	15 cm
Pivot	Yes
Pivot angle	0 - 90°
Swivelling	Yes
Swivel angle range	-60 - 60°
Tilt adjustment	Yes
Tilt angle range	-5 - 23°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Number of OSD languages	11

Power

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	21.4 kWh
Power consumption (typical)	26 W
Power consumption (standby)	0.4 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Weight & dimensions

Width (with stand)	613 mm
Depth (with stand)	209.5 mm
Height (with stand)	564.5 mm
Weight (with stand)	6.4 kg
Height (without stand)	414.5 mm

Packaging data

Package width	690 mm
Package depth	168 mm
Package height	457 mm

Package weight	8.2 kg
Package type	Box
USB cable length	1.8 m
Packaging content	
Stand included	Yes
Cables included	AC, USB, HDMI, DisplayPort
Quick start guide	Yes
DisplayPort cable length	1.8 m
HDMI cable length	1.8 m
Power cable length	1.8 m
Sustainability	
Sustainability certificates	ErP, TCO
Other features	
Brand specific technologies	Six Axis Control
Packaging content	quick start guide, safety guide
Weight	6.4 kg
Width	613 mm
Depth	209.5 mm
Compliance certificates	CE, EAC, PSE, REACH, RoHS, TÜV mark, UKCA, VCCI, WEEE
User controls	picture adjust (contrast, brightness, i-Style colour, ACR, Eco, OD, X-Res technology), image settings (blue light reducer, sharp and soft, video mode adjust), colour settings (gamma, 6-axis, colour temp.), audio settings (volume, mute), OSD settings (H. position, V. position, OSD time, OSD rotate, language), extra 1 (MBR, Adaptive Sync, USB-C, KVM, USB BC), extra 2 (reset, DDC/CI, signal select, HDMI range, opening logo, LED, information)
Control panel	Signal Select/ Exit (Input), + / Volume, - / Eco, Menu, Power
Matmenys ir svoris	
Svoris	8,10kg