

iiyama ProLite T1932MSC-B2X computer monitor 48.3 cm (19") 1280 x 1024 pixels LED Touchscreen Black

Gamintojas: **IIYAMA** · Modelis: **T1932MSC-B2X** · EAN: **4948570113736** · Prekės kodas: **634214**



278,91 €

Kaina su PVM

Be PVM: **230,50 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48.3 cm (19") Black
- ✓ Built-in speaker(s)
- ✓ Screen shape: Flat
- ✓ Response time: 14 ms
- ✓ 1280 x 1024 pixels Panel type: IPS



Aprašymas

The ProLite T1932MSC-B2X 19" multi touch screen is based on projective capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The IPS matrix guarantees high performance with accurate and consistent colour reproduction, and wide viewing angles. The touch function remains unaffected even if the glass is scratched. A solid and steady base supports the touch screen with an adjustable stand offering full 90 degree positioning angles. In addition the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours.

Techninė specifikacija

Specifications

Sandėlio grupė	Monitore [+1517][-101]
Display	
Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LED
Touchscreen	Yes
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.78 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Display brightness	225 cd/m²
Aspect ratio	5:4
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.294 x 0.294 mm
Horizontal scan range	31.4 - 80 kHz
Vertical scan range	56 - 75 Hz
Viewable size diagonal	48 cm
Display diagonal (metric)	48 cm
Separate H/V sync	Yes
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Number of simultaneous touchpoints (Windows 7)	10
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2

RMS rated power	2 W
Megapixel (approx.)	1.3 MP
Design	
Product colour	Black
Ports & interfaces	
Number of upstream ports	1
VGA (D-Sub) ports quantity	1
DVI port	Yes
DVI-D ports quantity	1
HDMI ports quantity	0
DisplayPorts quantity	0
Audio input	1
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Wall mountable	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	8
Plug and Play	Yes
LED indicators	Yes
Power	
Power consumption (typical)	20 W
Power consumption (standby)	2 W
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz
Power supply type	AC
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Dimensions (W x D x H) with stand	432 x 219 x 391 mm
Width (with stand)	432 mm
Depth (with stand)	219 mm
Height (with stand)	391 mm
Weight (with stand)	6.9 kg
Width (without stand)	432 mm
Depth (without stand)	54.5 mm
Height (without stand)	358 mm

Packaging content

Cables included	AC, AUX, USB, VGA
Quick start guide	Yes

Other features

International Protection (IP) code	IP54
Display viewable area (HxV)	376.5 x 301.1 mm
Power management	Yes
Certification	CE, CB, TÜV-Bauart, VCCI, CU, cULus
Supplied AC adapter type	AC

Logistics data

Harmonized System (HS) code	85285210
-----------------------------	----------