

TP-Link Omada EAP225-Outdoor 1200 Mbit/s White Power over Ethernet (PoE)

Gamintojas: **TP-LINK** · Modelis: **EAP225-OUTDOOR** · EAN: **1210002618519** · Prekės kodas: **634468**



86,90 €

Kaina su PVM

Be PVM: **71,82 €**

Neturime



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt



Aprašymas

Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux | Web-based management: Yes | 2.4 GHz: Yes | MIMO: Yes | Frequency band: 2.4 - 5 GHz | Product colour: White | Maximum data transfer rate: 1200 Mbit/s | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11b | 5 GHz: Yes | Ethernet LAN data rates: 1000 | Reset button: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3ab | Antenna type: External | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | Ethernet LAN data rates: 100 Mbit/s | Ethernet LAN data rates: 10 | Package weight: 640 g | AC adapter included: Yes | Package height: 100 mm | Service Set Identifier (SSID) features: Multiple SSIDs | Mounting kit: Yes | Antenna direction type: Omni-directional | VLAN support: Yes | Antennas quantity: 2 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package width: 140 mm | Ethernet LAN (RJ-45) ports: 1 | Number of SSID supported: 16 | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | 6 GHz: No | Operating relative humidity (H-H): 10 - 90% | Package depth: 270 mm | Depth: 46 mm | Airtime Fairness (ATF): Yes | Height: 27 mm | Rate limiting: Yes | Virtual LAN features: VLAN mapping | Output voltage: 24 V | International Protection (IP) code: IP65 | Band steering: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Power over Ethernet (PoE): Yes | Access Control List (ACL): Yes | MIMO type: Multi User MIMO | Placement: Pole, Wall | Quick start guide: Yes | Harmonized System (HS) code: 85176990 | Quantity per pack: 1 pc(s) | Storage relative humidity (H-H): 5 - 90% | Antenna features: Detachable antenna | Transmitting power (CE): 27 dBm | Width: 215 mm | Antenna gain level (max): 4 dBi | Transmitting power (FCC): 22 dBm | Maximum data transfer rate (5 GHz): 867 Mbit/s | Syslog: Yes | BeamForming: Yes | Operating temperature (T-T): -30 - 70 °C | Security algorithms: 802.1x RADIUS | Power consumption (typical): 10.5 W | Power over Ethernet (PoE) type supported: Passive PoE | Sustainability compliance: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

Techninė specifikacija

Specifications	
Sandėlio grupė	AccesPoint [+44][-36]
Matmenys ir svoris	
Matmenys (I × P × A)	28,00cm × 14,00cm × 10,00cm
Svoris	0,62kg