

TP-Link Omada ES208GP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Black

Gamintojas: **TP-LINK** · Modelis: **ES208GP** · EAN: **1210002609708** · Prekės kodas: **634469**



68,90 €

Kaina su PVM

Be PVM: **56,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8x 10/100/1000Mbps RJ45 ports (8x 802.3af/at-compliant PoE+)
- ✓ 64W Power Budget, with up to 30W for each PoE port*
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralized Cloud Management via the web or the Omada app†
- ✓ Up to 820ft PoE**, Remote Camera Reboot†, QoS, and Port Isolation for reliable surveillance networking
- ✓ Automatic Loop Prevention, VLAN, and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/wall mounting design



Aprašymas

Networking standards: IEEE 802.3at | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3bt | Networking standards: IEEE 802.3af | Ethernet LAN data rates: 10,100,1000 Mbit/s | Web-based management: Yes | Quick start guide: Yes | LED indicators: Yes | Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 0 - 40 °C | Input current: 1.31 A | Form factor: DIN rail | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Product colour: Black | Loop protection: Yes | Packet buffer memory: 0.5 MB | Total Power over Ethernet (PoE) budget: 64 W | MAC address table: 8000 entries | Auto-negotiation: Yes | Width: 158 mm | Virtual LAN features: Tagged VLAN | Multicast support: Yes | Switch layer: L2 | Cables included: Power | Port mirroring: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switching capacity: 16 Gbit/s | Auto MDI/MDI-X: Yes | VLAN support: Yes | Height: 25.4 mm | Forwarding rate: 11.904 Mpps | Rack mounting: Yes | Virtual LAN features: MTU VLAN | Power source: DC | IGMP snooping: Yes | Power over Ethernet

plus (PoE+) ports quantity: 8 | Depth: 100.7 mm | Virtual LAN features: Port-based VLAN | DHCP features: DHCP client | Broadcast storm control: Yes | Switch type: Managed | Link aggregation: Yes | Store-and-forward: Yes | Jumbo frames support: Yes | Storage relative humidity (H-H): 5 - 90% | Number of VLANs: 4000 | Flow control support: Yes | 10G support: No | Power over Ethernet (PoE) type supported: PoE+ | Jumbo frames: 15000 | DC input voltage: 53 V | Transmission distance (max): 0.25 km | Cloud-managed: Yes | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+88][-98]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
VLAN support	Yes
Virtual LAN features	MTU VLAN, Port-based VLAN, Tagged VLAN
Number of VLANs	4000
Optical fiber	
Transmission distance (max)	0.25 km
Data transmission	
MAC address table	8000 entries
Switching capacity	16 Gbit/s

Forwarding rate	11.904 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	0.5 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Loop protection	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Form factor	DIN rail
Product colour	Black
LED indicators	Yes
Power	
Power source	DC
DC input voltage	53 V
Input current	1.31 A
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Power over Ethernet plus (PoE+) ports quantity	8
Total Power over Ethernet (PoE) budget	64 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	158 mm
Depth	100.7 mm
Height	25.4 mm

Packaging content	
Cables included	Power
Quick start guide	Yes
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Matmenys ir svoris	
Matmenys (l × p × A)	23,00cm × 14,00cm × 12,00cm
Svoris	1,05kg