

Zyxel NWA50AX PRO 2400 Mbit/s White Power over Ethernet (PoE)

Gamintojas: ZYXEL · Modelis: NWA50AXPRO-EU0102F · EAN: 4718937630554 · Prekės kodas: 637055



88,90 €

Kaina su PVM

Be PVM: 73,47 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2.4 GHz 575 Mbit/s
- ✓ 5 GHz 2400 Mbit/s
- ✓ Maximum data transfer rate: 2400 Mbit/s
- ✓ IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
- ✓ WPA, WPA2, WPA3
- ✓ Power over Ethernet (PoE)
- ✓ Internal Integrated antenna



Aprašymas

Multi-gig WiFi 6 access point for small businesses

Zyxel NWA50AX Pro

AX3000 Dual-Radio Multi-gig PoE Access Point

Multi-gig WiFi 6 access point for small businesses

Delivering AX3000 WiFi speed with 2.5G Ethernet uplink port, the Zyxel NWA50AX Pro provides the powerful and fastest WiFi 6 speed for small

businesses, SoHo, and home offices.

Small business owners looking for an affordable WiFi 6 access point with multi-gig connectivity, Zyxel's NWA50AX Pro is no doubt the ideal choice for them to support more connected devices and applications with the fastest speeds.

Boost your WiFi performance

To better leverage the faster speeds in 5GHz band, Zyxel NWA50AX Pro equips with 3x high-gain antennas to boost WiFi signals and extend coverage, especially to previously hard-to-reach areas.

In addition to the WiFi boost, NWA50AX Pro also comes with the premium multi-gig Ethernet connections. As it can run on the common-type Cat5e cabling, a 2.5G uplink port breaks through the 1.0G bottleneck without re-cabling, making it easy to create an affordable high-speed network environment for your business or home.

Set up your wireless network in minutes!

No networking expertise required - The NWA50AX Pro is designed to be easily configured and installed in places like small hotels, retail stores, restaurants, or home offices.

The simple configuration allows you to set up the network for your customers and employees in minutes. The AP can be managed either with Nebula Cloud networking platform or the device's local interface.

Easy deployment with Zyxel's Smart Mesh

Zyxel's Smart Mesh technology automatically forms dynamic wireless links between access points and mitigates the complex, inconvenient cabling for WiFi deployment.

The Smart Mesh technology can save you from extra wiring by enabling the wireless connectivity between APs for extended range and flexible deployment.

Manage it your way!

The NWA50AX Pro with NebulaFlex offers the flexible manageability for you to freely choose between the device's local web interface or onboarding to our super easy Nebula cloud management interface that you never need to worry about forgetting the IP address or lost account and password when managing it on cloud.

Techninė specifikacija

Specifications	
Sandėlio grupė	Accesspoints [+302][-27]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	2400 Mbit/s
Maximum data transfer rate (2.4 GHz)	575 Mbit/s
Maximum data transfer rate (5 GHz)	2400 Mbit/s
Ethernet LAN data rates	1000,2500 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n

MIMO	Yes
MIMO type	Multi User MIMO
Wi-Fi Multimedia (WMM)/(WME)	Yes
VLAN support	Yes
Security	
Security algorithms	WPA, WPA2, WPA3
MAC address filtering	Yes
Protocols	
Management protocols	SNMP
Management features	
Web-based management	Yes
Firmware upgradeable	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
USB 2.0 ports quantity	0
DC-in jack	Yes
Power	
Power over Ethernet (PoE)	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	0.3 A
Output voltage	12 V
Output current	2 A
Design	
Placement	Ceiling
Product colour	White
LED indicators	Yes
Antenna	
Antenna type	Internal
Antenna features	Integrated antenna
Antenna gain level (max)	4 dBi
Weight & dimensions	
Width	140 mm
Depth	140 mm

Height	37.5 mm
Weight	352 g
Packaging data	
Package width	240 mm
Package depth	155 mm
Package height	60 mm
Package weight	668 g
Packaging content	
Quantity per pack	1 pc(s)
AC adapter included	Yes
Mounting kit	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	10 - 90%
Matmenys ir svoris	
Matmenys (I × P × A)	14,00cm × 14,00cm × 4,00cm
Svoris	0,67kg