

Zebra ZD621 label printer Thermal transfer 203 x 203 DPI 203 mm/sec Wired & Wireless Ethernet LAN Bluetooth

Gamintojas: ZEBRA · Modelis: ZD6A042-32EF00EZ · EAN: 5704174529446 · Prekės kodas: 638140



727,90 €

Kaina su PVM

Be PVM: 601,57 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Thermal transfer
- ✓ 203 x 203 DPI
- ✓ Maximum printing width: 10.4 cm Print speed: 203 mm/sec
- ✓ Connectivity technology: Wired & Wireless
- ✓ USB port Ethernet LAN Bluetooth 5.0
- ✓ 2.5 kg

Aprašymas

INVEST IN THE BEST: PREMIUM FEATURES, MAXIMUM PERFORMANCE AND UNMATCHED SECURITY

You need a quality, long-lasting printer with top-of-the-line features to keep your business moving forward. Select Zebra's ZD600 Series 4-inch premium desktop printers, built to perform flawlessly – day in and day out. Easy to operate, they include Zebra's exclusive Print DNA software suite that makes them simple to set up, manage and secure – onsite or remotely. And, they're engineered for evolving technology for years of operation. Unlike other brands, Zebra's printers give you peace-of-mind security with PrintSecure, part of Print DNA, to prevent downtime and costly cyberattacks. Choose from direct thermal, thermal transfer, healthcare and RFID models.

Techninė specifikacija

Specifications

Sandėlio grupė Drucker [+434][-35]

Printing

Print technology Thermal transfer

Maximum resolution 203 x 203 DPI

Print speed	203 mm/sec
Maximum printing width	10.4 cm
Paper handling	
Maximum label length	0.991 m
Media thickness	0.08 - 0.19 mm
Ports & interfaces	
Connectivity technology	Wired & Wireless
Ethernet LAN	Yes
USB port	Yes
Bluetooth	Yes
Bluetooth version	5
Bluetooth Low Energy (BLE)	Yes
Performance	
Page description languages	EPL2, XML, ZBI, ZPL II
Internal memory	256 MB
Flash memory	512 MB
Design	
Product colour	Grey
Control type	Buttons
Power	
AC input voltage	100 - 240 V
AC input frequency	50-60 Hz
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 95%
Operating temperature (T-T)	4.4 - 41 °C
Storage temperature (T-T)	-40 - 60 °C
Weight & dimensions	
Width	202 mm
Depth	267 mm
Height	192 mm
Weight	2.5 kg
Logistics data	
Harmonized System (HS) code	84433210