

Zebra DS2208-HC Handheld bar code reader 1D/2D LED White

Gamintojas: **ZEBRA** · Modelis: **DS2208-HC0000BZZRW** · EAN: **8596375197411** · Prekės kodas: **638155**



150,90 €

Kaina su PVM

Be PVM: **124,71 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Handheld bar code reader White
- ✓ Scanner type: 1D/2D Sensor type: LED
- ✓ Codabar, Code 11, Code 128, Code 39, Code 93, EAN 128, EAN 2, EAN 5, EAN-13, EAN-8, MSI, U.P.C., UPC-A, UPC-E
- ✓ 640 x 480 pixels
- ✓ Tilt reading angle: 0 - 360°
- ✓ Wired Standard interfaces: Keyboard wedge, RS-232, USB
- ✓ Power source type: RS-232, USB



Aprašymas

IMPROVE PATIENT SAFETY AND CLINICIAN PRODUCTIVITY

Purpose-built for healthcare, you get an affordable imager that doesn't compromise performance or features for price. Capture the many kinds of barcodes commonly used in hospitals—from barcodes on patient wristbands and medication vials to IV bags and specimen trays. Pre-configured and ready to use right out of the box, the scanner is configured for the healthcare applications you use every day, while auto-host detect cables automatically select the right host interface—just plug in the scanner and you're ready to go.

Techninė specifikacija

Specifications

Sandėlio grupė	Scanner [+571][-31]
Scanning	
Type	Handheld bar code reader
Scanner type	1D/2D
Sensor type	LED
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 39, Code 93, EAN 128, EAN 2, EAN 5, EAN-13, EAN-8, MSI, U.P.C., UPC-A, UPC-E
Optical sensor resolution (W x H)	640 x 480 pixels
Light levels (direct sunlight)	0 - 107600 lx
Wavelength	624 nm
Tilt reading angle	0 - 360°
Pitch reading angle	0 - 65°
Yaw reading angle	0 - 65°
Ports & interfaces	
Connectivity technology	Wired
Standard interfaces	Keyboard wedge, RS-232, USB
Performance	
Product colour	White
International Protection (IP) code	IP52
LED indicators	Yes
Buzzer	Yes
Certification	RoHS EN 50581, EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/ CSA-C22.2 No. 60950-1-07, IEC 62471, EN 55032 (Class B), EN 55024, EN 61000-3-2, EN 61000-3-3, 47 CFR Part 15, Subpart B, Class B, ICES-003 Issue 6, Class B
Power	
Power source type	RS-232, USB
Input voltage	4.5 - 5.5 V
Weight & dimensions	
Weight	161.6 g
Width	66 mm
Depth	99 mm
Height	165 mm
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C

Operating relative humidity (H-H)	5 - 95%
-----------------------------------	---------

Logistics data

Harmonized System (HS) code	84716070
-----------------------------	----------

Matmenys ir svoris

Svoris	0,23kg
--------	--------