

Samsung OM32DX 81.3 cm (32") LCD Wi-Fi 2000 cd/m² Full HD Black Tizen 24/7

Gamintojas: **SAMSUNG** · Modelis: **LH32OMDEBGBXEN** · EAN: **8806095813363** · Prekės kodas: **639085**



1 566,90 €

Kaina su PVM

Be PVM: **1 294,96 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ High Brightness
- ✓ Slim Depth

- ✓ IP5X & Overheating Mitigation



Aprašymas

Bring in customers with captivating displays

Samsung Window Signage adds a stunning display to your storefront. Featuring high brightness and clarity, even in direct sunlight, the display makes your messages stand out. The slim design maximizes space utilization while creating captivating and engaging customer experiences.

Clear and vivid displays in any light

High Brightness

Enjoy 2000-nit brightness for outdoor visibility—even in direct sunlight and for viewers wearing sunglasses—the OM32DX delivers clear, vivid content. A built-in sensor automatically adjusts brightness levels to match changing light conditions.

Maximum impact in minimum space

Slim Depth

An ultra-slim Window Signage with a thickness of 45.6mm makes the OM32DX conveniently thin. Its thinness allows for installation in various

environments with a clean look. The sleek design maximizes the display's impact, integrating seamlessly into your business setting.

Clean visuals in landscape or portrait mode

Even Bezel

The OM32DX boasts an even bezel design where the thickness of all four bezels are consistent. Regardless of whether it is installed horizontally or vertically, this symmetrical design offers an aesthetic balance that adds stability to your visuals.

Operate smoothly

IP5X & Overheating Mitigation

With IP5X-validated dust protection and embedded, proprietary functionality that mitigates overheating, Samsung window display helps you meet your needs. Enjoy optimized operation in a variety of conditions for consistent performance.

Convenient, clean display control

Embedded Wi-Fi

Built-in Wi-Fi allows for wireless remote management of both content and display, streamlining operations and enhancing convenience. This function eliminates the need for cumbersome cables and enables real-time updates, giving users greater control over their signage setup.

Empower your business with smart control

SmartThings Pro

Samsung SmartThings now extends beyond the home, integrating into business environments. SmartThings Pro connectivity delivers convenience across various business settings, from small personal shops to large companies and hotels.

Change the way to manage your display

Samsung VXT

The cloud-based Samsung VXT brings together content management and remote device management capabilities, allowing you to remotely manage hardware settings and troubleshoot issues while effortlessly creating and deploying content with no previous training needed.

Techninė specifikacija

Specifications	
Sandėlio grupė	Large Format Displays [+219][-44]
Display	
Display diagonal	81.3 cm (32")
Display technology	LCD
Display resolution	1920 x 1080 pixels
Display brightness	2000 cd/m ²
HD type	Full HD
Touchscreen	No
Panel type	VA
Response time	8 ms
Contrast ratio (typical)	4000:1
Dynamic contrast ratio marketing name	Mega Contrast
Viewing angle, horizontal	178°
Viewing angle, vertical	178°

Pixel pitch	0.3637 x 0.3637 mm
Haze rate	0%
Pixel frequency (max)	594 MHz
Colour gamut	72%
Ports & interfaces	
HDMI ports quantity	2
DVI port	No
DisplayPorts quantity	0
USB port	Yes
HDMI version	2
Ethernet LAN (RJ-45) ports	2
RS-232 interface	Yes
Remote (IR) input	1
Audio	
Built-in speaker(s)	No
Design	
Product colour	Black
Placement supported	Indoor/outdoor
VESA mounting	Yes
Screen shape	Flat
Panel mounting interface	100 x 100 mm
Performance	
Operating hours (hours/days)	24/7
HDCP	Yes
HDCP version	2.2
Power	
Power consumption (typical)	140 W
Power consumption (standby)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Computer system	
Operating system installed	Tizen
Operating system version	8
Weight & dimensions	

Display width	732.5 mm
Display depth	45.6 mm
Display height	426.9 mm
Display weight	7.6 kg
Packaging data	
Package width	820 mm
Package depth	127 mm
Package height	512 mm
Package weight	9.7 kg
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Technical details	
Compliance certificates	Electromagnetic Compatibility (EMC)
Audio out (mini jack)	1
Other features	
Bluetooth	Yes
Display sRGB	Yes
Flash memory	8000 MB
RS-232 input ports	1
RS-232 output ports	1
Matmenys ir svoris	
Svoris	9,91kg