Zebra ZT610 label printer Thermal transfer 300 x 300 DPI 300 mm/sec Wired & Wireless Ethernet LAN Bluetooth

Gamintojas: **ZEBRA** · Modelis: **ZT61043-T0E01C0Z** · EAN: **8596375178335** · Prekės kodas: **639151**

3 005,89 €

Kaina su PVM

Be PVM: **2 484,21 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Thermal transfer
- ✓ 300 x 300 DPI
- ✓ Maximum printing width: 10.4 cm Print speed: 300 mm/sec
- ✓ Built-in barcodes: 1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, Micro QR Code, MicroPDF417, PDF417, POSTNET, QR Code, TLC39, UPC-A, UPC-E
- ✓ Connectivity technology: Wired & Wireless
- ✓ USB port Ethernet LAN Bluetooth 4.0
- ✓ Display: LCD 10.9 cm (4.3") Colour display
- ✓ 22.7 kg

Aprašymas

THE NEXT GENERATION XI SERIES, NOW WITH MORE INTELLIGENCE AND INDUSTRIAL BRAWN

The ZT600 Series advances the legacy of the Xi Series printers to combine rugged durability and exceptional performance on a user-friendly, future-ready platform. These next-generation workhorses are designed to help you navigate the rapidly evolving business landscape. So, whether you’re concerned about growing production line demands, increasing operational complexities, integrating disparate systems or controlling investment costs, the ZT600 Series industrial printers have you covered today – and for years to come.

EXCEPTIONAL PERFORMANCE FROM MICRO LABELS TO HIGH-VOLUME SHIPPING

Boost your productivity with printers that just won’t quit. The ZT600 Series features durable steel structural components that can withstand years of abuse in extreme temperatures, dust, debris and other challenging industrial conditions. Meticulously engineered printing mechanisms provide 24/7 reliability to meet your high-volume production needs. Plus, the ZT610™ offers best-in-class print registration with 600 dpi micro consistent printing.

HASSLE-FREE SETUP, DAILY USE, MAINTENANCE AND TROUBLESHOOTING

From color-illuminated media and ribbon paths that help you identify problems quickly to easy-adjust printhead pressure toggles that feature a scale

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

and color-coded pressure indicators to simplify printer setup and operation, every detail of the ZT600 Series was designed to be user-friendly. Side loading capabilities eliminate the hassles of threading. Onboard sensors, diagnostics and help resources reduce the need for technical support. And guided instructions and feedback prevent common errors and reduce manual adjustments for highly consistent printing.

OPERATIONAL VISIBILITY, REMOTE MANAGEMENT AND FUTURE-READY ADAPTABILITY

The ZT610 and ZT620 are as smart as they are powerful. Zebra’s cloud-accessible Link-OS™ software platform and managed services offerings give you total visibility and control over your printing systems, whether you’re on-site or across the globe. Plus, with two available communication slots, field-installable RFID encoder and media-handling options, and two USB host ports for plug-and-play integration, it’s easy to stay ahead of your evolving business and technology needs, whatever they may be.

Techninė specifikacija

Specifications	
Sandėlio grupė	Drucker [+509][-41]
Printing	
Print technology	Thermal transfer
Maximum resolution	300 x 300 DPI
Print speed	300 mm/sec
Maximum printing width	10.4 cm
Vertical printing	Yes
Rotated printing	Yes
Paper handling	
Ribbon width	11 cm
Ribbon length	450 m
Maximum label length	762 m
Maximum roll diameter	20.3 cm
Media thickness	0.058 - 0.25 mm
Core diameter	7.62 cm
Ports & interfaces	
Connectivity technology	Wired & Wireless
Ethernet LAN	Yes
Wi-Fi	No
USB port	Yes
Bluetooth	Yes
Bluetooth version	4
USB 2.0 ports quantity	3
RS-232 ports	1
Performance	

Page description languages	ZPL, ZPL II
Internal memory	1024 MB
Flash memory	2048 MB
Built-in barcodes	1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, Micro QR Code, MicroPDF417, PDF417, POSTNET, QR Code, TLC39, UPC-A, UPC-E
Built-in processor	Yes
Number of fonts	16
Built-in RFID module	Yes
Processor frequency	800 MHz
Design	
Product colour	Black, Grey
Display	LCD
Built-in display	Yes
Display diagonal	10.9 cm (4.3")
Colour display	Yes
Housing material	Metal
Power	
AC input voltage	90 - 265 V
AC input frequency	47-63 Hz
Operational conditions	
Operating relative humidity (H-H)	20 - 85%
Storage relative humidity (H-H)	20 - 85%
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-30 - 60 °C
Weight & dimensions	
Width	268.2 mm
Depth	505 mm
Height	395.7 mm
Weight	22.7 kg
Logistics data	
Harmonized System (HS) code	84433210
Technical details	
Sustainability certificates	ENERGY STAR
Other features	

Navigation key	Yes
Plug and Play	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.
www.shopro.lt · info@shopro.lt · +370 693 39903