

Zebra TC58 handheld mobile computer 15.2 cm (6") 1080 x 2160 pixels Touchscreen 293 g Black

Gamintojas: **ZEBRA** · Modelis: **TC58B1-3T1E4B1080-A6** · EAN: **5715063000946** · Prekės kodas: **639461**



2 575,90 €

Kaina su PVM

Be PVM: **2 128,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 15.2 cm (6") 1080 x 2160 pixels Touchscreen
- ✓ 4 GB
- ✓ Compatible memory cards: MicroSD (TransFlash)
- ✓ 2.7 GHz
- ✓ GPS (satellite) Android
- ✓ Bluetooth Bluetooth Low Energy (BLE) Data network: 5G, LTE Near Field Communication (NFC) Wi-Fi
- ✓ Built-in camera 16 MP
- ✓ Lithium-Ion (Li-Ion) 4400 mAh
- ✓ Black



Aprašymas

TC5X Series Mobile Computers

The Ultimate in Rugged Design, Performance, Productivity and Ease of Use

The TC5X Series - the Wi-Fi only TC52x with Wi-Fi 5 (802.11ac), the Wi-Fi only TC52ax with Wi-Fi 6, and the Wi-Fi 5/cellular TC57x deliver the ultimate in rugged design, performance, and ease of use. The TC53/TC58, the new generation of the Zebra TC5X series mobile computers, is designed to do more with new hardware and software innovations that redefine mobile computing performance. No matter which models you choose, your workers get a user experience in a class of its own and all the latest technology advancements to work smarter — and faster.

Benefits of the TC5X Series

The Ultimate User Experience

The TC5X Series mobile computers have it all — from the familiarity of Android to the first-time every-time capture of barcodes, more Wi-Fi range and speed, video streaming, secure messaging, and the most powerful family of read-to-use voice solutions.

The Ultimate in Technology Advancements

You get maximum computing power to handle the apps of today and tomorrow, rich locationing support, more reliable Wi-Fi connections; high-quality voice; color cameras to capture ultra-high resolution photos and video intelligence and much more.

The Ultimate in Value-add Features

With Zebra's powerful Mobility DNA suite, you get more value out of your mobile computers by adding functionality as well as simplifying deployment and management of your mobile devices, driving productivity and device control to a new level.

Techninė specifikacija

Specifications	
Sandėlio grupė	Scanner [+632][-34]
Display	
Display diagonal	15.2 cm (6")
Display resolution	1080 x 2160 pixels
Touchscreen	Yes
Touch technology	Multi-touch
Touchscreen type	Capacitive
Display brightness	600 cd/m²
Display glass type	Gorilla Glass
Memory	
Internal memory	4 GB
Flash memory	64 GB
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	2 TB
Processor	
Processor frequency	2.7 GHz
Processor manufacturer	Qualcomm
Built-in processor	Yes
Network	
Wi-Fi	Yes

Bluetooth	Yes
Data network	5G, LTE
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)
Bluetooth version	5.2
Bluetooth Low Energy (BLE)	Yes
SIM card type	NanoSIM
Security algorithms	EAP-AKA, EAP-PWD, EAP-SIM, EAP-TLS, EAP-TTLS, LEAP, MSCHAPv2, WEP, WPA-Enterprise, WPA-TKIP, WPA2-AES, WPA2-Enterprise, WPA2-TKIP, WPA3-Enterprise, WPA3-SAE
Near Field Communication (NFC)	Yes
GPS Performance	
GPS (satellite)	Yes
Assisted GPS (A-GPS)	Yes
GLONASS	Yes
BeiDou	Yes
Galileo	Yes
Camera	
Built-in camera	Yes
Rear camera resolution (numeric)	16 MP
Front camera	Yes
Front camera resolution (numeric)	8 MP
Built-in flash	Yes
Video recording	Yes
Audio	
Number of microphones	3
Noise-canceling	Yes
Speakers	stereo
Ports & interfaces	
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
Headphone outputs	1
Headphone connectivity	3.5 mm
Performance	
Product colour	Black
Barcode reader	Yes

Sensors	
Ambient light sensor	Yes
Accelerometer	Yes
Proximity sensor	Yes
Gyroscope	Yes
Magnetometer	Yes
Pressure sensor	Yes
Software	
Operating system installed	Android
Power	
Battery capacity	4400 mAh
Battery technology	Lithium-Ion (Li-Ion)
Weight & dimensions	
Weight	293 g
Width	77.3 mm
Depth	16.8 mm
Height	164.8 mm
Operational conditions	
Operating relative humidity (H-H)	5 - 95%
Operating temperature (T-T)	-20 - 50 °C
Storage temperature (T-T)	-40 - 70 °C