

PowerWalker VFI 3000 ICT IoT Double-conversion (Online) 3 kVA 3000 W 9 AC outlet(s)

Gamintojas: **POWER WALKER** · Modelis: **VFI 3000 ICT IOT PF1** · EAN: **4260074982862** · Prekės kodas: **639533**



728,90 €

Kaina su PVM

Be PVM: **602,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Battery capacity: 9 Ah | Emergency Power Off (EPO): Yes | Weight: 26.4 kg | Display type: LCD | Serial ports quantity: 1 | USB port: Yes | Output operation voltage (min): 200 V | Width: 192 mm | Number of batteries supported: 6 | Package height: 475 mm | Product colour: Black | Serial interface: Yes | Harmonized System (HS) code: 85078000 | Input frequency: 40/70 Hz | Output power: 3000 W | Output voltage Total Harmonic Distortion (THD): 1% | Charging current: 1.5 A | Output power factor: 1 | UPS topology: Double-conversion (Online) | Crest factor: 3:1 | AC outlets quantity: 9 AC outlet(s) | Input power factor: 0.99 | Cooling type: Active | Waveform: Pure sine | Serial interface type: RS-232 | Package width: 590 mm | Input operation voltage (min): 160 V | Power plug: C20 coupler | Built-in fan: Yes | AC outlet types: C19 coupler | Operating relative humidity (H-H): 0 - 95% | LED indicators: Yes | Input operation voltage (max): 300 V | Battery voltage: 12 V | Depth: 428 mm | Emergency Power Off (EPO) connector: Yes | Manual: Yes | Operating temperature (T-T): 0 - 45 °C | Cables included: Input power cable, Output power cable, USB cable | Input current Total Harmonic Distortion (THD): 5% | Height: 318 mm | ECO mode: Yes | Form factor: Tower | Output power capacity: 3 kVA | Output voltage regulation: 1% | Noise level: 50 dB | Power protection features: Overload | AC outlet types: C13 coupler | Battery recharge time: 3 h | Output operation voltage (max): 240 V

Techninė specifikacija

Matmenys ir svoris

Matmenys (I × P × A)

33,00cm × 60,00cm × 48,00cm

