

PowerWalker VI 2000 RLP Line-Interactive 2 kVA 1800 W 8 AC outlet(s)

Gamintojas: **POWER WALKER** · Modelis: **VI 2000 RLP** · EAN: **4260074983791** · Prekės kodas: **639534**



587,90 €

Kaina su PVM

Be PVM: **485,87 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Output voltage regulation: 10% | RS-232 ports: 1 | Battery recharge time: 4 h | Number of output phases: 1 | Operating temperature (T-T): 0 - 40 °C | Emergency Power Off (EPO): Yes | UPS topology: Line-Interactive | Response time: 6 ms | Output power capacity: 2 kVA | AC outlet types: C13 coupler | SmartSlot: Yes | Typical backup time at half load: 9 min | Operating relative humidity (H-H): 5 - 90% | Efficiency (ECO mode): 83.4% | Product colour: Black | Output power: 1800 W | USB port: Yes | Automatic Voltage Regulation (AVR): Yes | AC outlets quantity: 8 AC outlet(s) | Automatic battery test: Yes | Battery voltage: 12 V | Display type: LCD | Noise level: 40 dB | Output voltage Total Harmonic Distortion (THD): 3% | Input frequency: 45/65 Hz | Cold start: Yes | Rack capacity: 2U | Nominal output voltage: 230 V | Input operation voltage (min): 165 V | Power protection features: Overload | Charging current: 6 A | Waveform: Pure sine | International Protection (IP) code: IP20 | ECO mode: Yes | LED indicators: Yes | Power plug: C14 coupler | Input operation voltage (max): 290 V | Number of input phases: 1 | Efficiency (On-line mode): 98.8% | Typical backup time at full load: 2 min | Form factor: Rackmount/Tower | Battery capacity: 9 Ah | Number of batteries supported: 4 | USB port type: USB Type-B | Output power factor: 0.9 | Off-mode charging: Yes | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water.

Techninė specifikacija

Matmenys ir svoris

Matmenys (I × P × A)

56,00cm × 22,00cm × 55,00cm

Svoris

27,30kg