

iiyama LH10551UWS-B1AG Signage Display Digital signage flat panel 2.67 m (105") LED 500 cd/m² UltraWide 5K HD Black 24/7

Gamintojas: **IIYAMA** · Modelis: **LH10551UWS-B1AG** · EAN: **4948570121977** · Prekės kodas: **640046**



6 048,90 €

Kaina su PVM

Be PVM: **4 999,09 €**

[Sandėlyje](#)




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 21:9 Ultra-Wide Screen
- ✓ 5K - 11 Mega Pixels
- ✓ USB-C Connection



Aprašymas

Experience a true 21:9 Panoramic Ultra-Wide view for all your content with the jaw dropping 105" displays of iiyama. This super sleek thin bezel design display shows vibrant and larger than life imagery and videos using 5KUW resolution to make the difference. Whether installed in mission critical control room facilities or vibrant digital signage for high end retail spaces, this iiyama 105" large format display offers businesses an easy and effective solution to help capture their audience's attention. Designed to perform in continual, around the clock environments, the LH10551UWS-B1AG can be installed and utilised in landscape and portrait orientation to create the most stimulating imagery in any space.

Techninė specifikacija

Specifications

Sandėlio grupė

Large Format Displays [+221][-36]

Display

Display diagonal	2.67 m (105")
Display technology	LED
Display resolution	5120 x 2160 pixels
Display brightness	500 cd/m²
HD type	UltraWide 5K HD
Panel type	IPS
Native aspect ratio	21:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.479 x 0.479 mm
Active display area (W x H)	2450 x 1033.6 mm
Display diagonal (metric)	265.9 cm
Horizontal scan range	30 - 140 kHz
Native refresh rate	60 Hz
Haze rate	25%

Ports & interfaces

HDMI ports quantity	1
DisplayPorts quantity	1
USB port	Yes
HDMI version	2
HDMI input ports quantity	1
DisplayPorts out	1
USB ports quantity	4
USB version	2
USB Type-C DisplayPort Alternate Mode	Yes
Ethernet LAN (RJ-45) ports	1
Audio (L/R) in	1
Audio (L/R) out	1
RS-232C	Yes
OPS module slot	Yes

Audio

Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Screen shape	Flat
Panel mounting interface	1500 x 600 mm
Bezel colour	Black
Anti-glare screen	Yes
Performance	
Purpose	Universal
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, Czech, German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Russian
Operating hours (hours/days)	24/7
HDCP	Yes
HDCP version	2.2
Mean time between failures (MTBF)	50000 h
Power	
Power consumption (typical)	247 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	247 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Weight & dimensions	
Display width	2487.4 mm
Display depth	99.1 mm

Display height	1070.6 mm
Display weight	60.1 kg
Width	2487.4 mm
Depth	99.1 mm
Height	1070.6 mm
Weight	60.1 kg
Packaging data	
Package width	2683 mm
Package depth	339 mm
Package height	1407 mm
Package weight	88.7 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	AC, HDMI, RS-232
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Network	
Ethernet LAN	Yes
Technical details	
Sustainability certificates	ErP
Compliance certificates	CB, CE, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
Daisy Chain DisplayPort	Yes
User controls	picture (brightness, contrast, sharpness), Audio (treble, bass, balance, speakers, volume), OSD setup (language, OSD H-Position, OSD V-position, transparency, OSD timeout, OSD rotation), advanced settings (colour temp., custom colour temp., gamma), general settings (power management, LED, RC lock, picture format, factory reset), other settings (source input, DP-OUT mirror, LAN, SW version)
Other features	
Quick start guide	Yes
Power supply type	Internal
Plug and Play	Yes