

LG 49UH5Q-E Signage Display Digital signage flat panel 124.5 cm (49") LCD Wi-Fi 500 cd/m² 4K Ultra HD Black WebOS

Gamintojas: **LG** · Modelis: **49UH5Q-E** · EAN: **8806096540695** · Prekės kodas: **641014**



753,90 €

Kaina su PVM

Be PVM: **623,06 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Resolution : 3,840 × 2,160 (UHD)
- ✓ Brightness : 500 nits (Typ.)
- ✓ Bezel Width : 11.4 mm (Even Bezel)
- ✓ webOS Smart Platform
- ✓ LG Shield



Aprašymas

UHD Signage Display with LG webOS Platform and Advanced Security

Superb Picture Quality with Ultra HD Resolution

With the resolution of UHD, it makes the colors and details of the content vivid and realistic. In addition, the wide viewing angle provides clear content.

Even & Slim Bezel Design

The UH5Q series features perfectly balanced horizontal and vertical slim bezels, creating a visually harmonious display solution. Its specialized design simplifies installation in retail environments while delivering a truly immersive viewing experience.

Convenient webOS Platform

The UH5Q is equipped with a high-performance SoC that allows for multiple tasks to be performed without a separate media player. The webOS platform provides app development tools with an intuitive UI that enhances user convenience, and includes webOS partner apps to create an SI-friendly environment.

Design for Space Utilization

Designed with thin bezels and simple cable management, the UH5Q saves space. With specialized hidden power inlets, it can be installed close to the wall, leaving only about 13.5 mm of space with the slim bracket.

Durability that Provides Reliability

Optimized for business environments, the UH5Q is protected against salt, dust, iron powder and humidity thanks to conformal partial coating on power board, allowing for stable operation. Also, its customer-centric features, such as IP5x and Shock Monitoring, provide both reliability and satisfaction.

Comprehensive Security

webOS Signage goes beyond security measures at the operating system (OS) level. LG Shield employs a five-tiered defense system, encompassing server, application, operating system, system, and hardware. Each layer operates independently, providing comprehensive protection against various threats. Also webOS platform support ETSI EN 303 645.

SuperSign Solutions

SuperSign is an integrated and intuitive content management solution for creative and organized digital signage content in your space, connecting customers to a range of services with convenient user experiences. There are a variety of versions such as SuperSign Cloud, so discover and enjoy the version that best fits you.

Techninė specifikacija

Specifications	
Sandėlio grupė	Large Format Displays [+221][-37]
Display	
Display diagonal	124.5 cm (49")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m ²
HD type	4K Ultra HD
Touchscreen	No
Panel type	IPS
LED backlight	Yes
LED backlighting type	Edge-LED
Native aspect ratio	16:9
Contrast ratio (typical)	1100:1
Contrast ratio (dynamic)	1000000:1
Display number of colours	1.07 billion colours

Rated lifetime	50000 h
Native refresh rate	60 Hz
Ports & interfaces	
HDMI ports quantity	3
DVI port	No
DisplayPorts quantity	1
USB port	Yes
USB ports quantity	2
USB version	2
Ethernet LAN (RJ-45) ports	1
RS-232C	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Panel mounting interface	300 x 300 mm
Bezel width (bottom)	1.14 cm
Bezel width (side)	1.14 cm
Bezel width (top)	1.14 cm
Performance	
Purpose	Universal
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Swedish, Turkish
HDCP version	1.4/2.2
Power	
Power consumption (typical)	83 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.5 W

Power consumption (max)	134 W
Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	86.5 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Heat dissipation	283 BTU/h
Computer system	
Internal memory	16 GB
Operating system installed	WebOS
Operating system version	8
Weight & dimensions	
Display width	1104.3 mm
Display depth	29.7 mm
Display height	635.5 mm
Display weight	11.4 kg
Width (with stand)	1215 mm
Depth (with stand)	142 mm
Height (with stand)	742 mm
Weight (with stand)	14.2 kg
Packaging data	
Package weight	14.2 kg
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Features	
Heat dissipation (max)	457 BTU/h
Technical details	
Sustainability certificates	ENERGY STAR, ErP
Compliance certificates	CE, Federal Communications Commission (FCC), KC
Other features	

Internal memory type	eMMC
----------------------	------

Power supply type	Internal
-------------------	----------

Matmenys ir svoris

Matmenys (l × P × A)	122,00cm × 14,00cm × 75,00cm
----------------------	------------------------------