

TP-Link Omada AC1200 Wireless MU-MIMO Gigabit Wall-Plate Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP230-WALL** · EAN: **6935364089481** · Prekės kodas: **641046**



87,89 €

Kaina su PVM

Be PVM: **72,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Fast Dual-Band Wi-Fi: Simultaneous 300 Mbps on 2.4 GHz and 867 Mbps on 5 GHz totals 1,167 Mbps Wi-Fi speeds with MU-MIMO.†
- ✓ Gigabit Ports: 2 Gigabit Ethernet ports (1× uplink + 1× downlink)
- ✓ Integrated into Omada SDN: Zero-Touch Provisioning (ZTP)‡, Centralized Cloud Management, and Intelligent Monitoring
- ✓ Centralized Management: Cloud access and Omada app for ultra convenience and easy management
- ✓ Private Connection for Every Room: Designed to meet every network need in environments with numerous separated rooms, like hotels, offices, and dormitories
- ✓ Elegant Appearance: Unprecedented thin design with just 11 mm, the same size and shape as a light switch or power outlet faceplate to fit perfectly in any room
- ✓ Easy Installation and PoE Support: Easy-mount construction, compatible with 86 mm & EU standard junction box, and 802.3af/at PoE support
- ✓ Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies



Aprašymas

Unprecedented Thin Design with 11mm
Omada EAP230-Wall
AC Access Point

Private Connection for Every Room.

EAP230-Wall is designed to meet every network need in environments with numerous separated rooms, like hotels, offices, and dormitories. A device in each room ensures an exclusive, high-speed Wi-Fi connection for every user.

MU-MIMO + Dual-Band: Faster Connection for More Devices

802.11ac wave 2 technology allows multiple users to access the internet at the same time. Speeds up to 1200 Mbps and 2.4 GHz and 5 GHz wireless bands deliver simultaneous high-speed internet access to various devices.

Seamlessly Blends with any Décor

The same size and shape as a light switch or power outlet faceplate to fit in perfectly in any room.

High-Speed Gigabit Port

Equipped with a Gigabit port to deliver the fastest possible wired transmission.

Effortless Deployment with Power over Ethernet

802.3af/802.3at PoE support means there's no need for extra wiring. Plug in existing Ethernet cables to transmit both power and data to your APs.

Quick, Simple Installation

1. Detach and remove the faceplate of the junction box.
2. Plug an Ethernet cable in to the port.
3. Secure the Access Point to the wall using the provided screws.
4. Press the faceplate back into position.

Omada SDN—Smarter Cloud Solution for Business Networking

Omada Software Defined Networking (SDN) platform integrates network devices including access points, switches and gateways, guaranteeing powerful business network with higher efficiency, higher security, and higher reliability.

Easy Management with the Omada App

Follow configuration instructions on the free Omada app to get set up in minutes. Omada lets you configure settings, monitor the network status and manage clients, all from the convenience of a smart phone or tablet.

Techninė specifikacija

Specifications	
Sandėlio grupė	Accesspoints [+304][-18]
Features	
2.4 GHz	Yes
5 GHz	Yes
6 GHz	No
Maximum data transfer rate	1167 Mbit/s
Maximum data transfer rate (2.4 GHz)	300 Mbit/s
Maximum data transfer rate (5 GHz)	867 Mbit/s

Ethernet LAN data rates	10,100,1000 Mbit/s
Frequency band	2.4 - 5 GHz
Networking standards	IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3af, IEEE 802.3at
Cabling technology	10/100/1000Base-T(X)
Automatic channel selection	Yes
Automatic channel scanning	Yes
MIMO	Yes
MIMO type	Multi User MIMO
Wi-Fi Multimedia (WMM)/(WME)	Yes
VLAN support	Yes
Virtual LAN features	Port-based VLAN, VLAN mapping
Rate limiting	Yes
Band steering	Yes
Quality of Service (QoS) support	Yes
BeamForming	Yes
Transmitting power (CE)	20 - 23 dBm
Security	
Security algorithms	64-bit WEP, 128-bit WEP, 152-bit WEP, SNMP, SNMPv2, WPA, WPA-PSK, WPA2-Enterprise, WPA2-PSK
MAC address filtering	Yes
Service Set Identifier (SSID) features	Multiple SSIDs
Number of SSID supported	16
Access Control List (ACL)	Yes
Management features	
Web-based management	Yes
Syslog	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
WAN connection	Ethernet (RJ-45)
Power	
Power over Ethernet (PoE)	Yes
Power consumption (typical)	9 W
Power consumption (max)	25.5 W
Design	
Placement	Wall

Product colour	White
Reset button	Yes
LED indicators	Operation
Antenna	
Antenna type	Internal
Antenna features	Integrated antenna
Antennas quantity	2
Antenna gain level (max)	3.6 dBi
Performance	
Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10
Certificates	
Compliance certificates	CE, RoHS
Weight & dimensions	
Width	86.8 mm
Depth	86.8 mm
Height	30.2 mm
Packaging data	
Package width	118 mm
Package depth	130 mm
Package height	47 mm
Package weight	210 g
Packaging content	
Quantity per pack	2 pc(s)
Mounting kit	Yes
Quick start guide	Yes
Operational conditions	
Operating relative humidity (H-H)	10 - 90%
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%
Logistics data	
Harmonized System (HS) code	85176990
Sustainability	
Sustainability compliance	Yes

Matmenys ir svoris

Svoris	0,22kg
--------	--------